



LED Side Light Recessed Troffer (SLI)



The **LED SLI** is a low-profile troffer that provides balanced illumination from the sides of the fixture. This results in superior low angle brightness control.

- Available in 2x2 and 2x4 sizes
- Choice of 12 lumen outputs - up to 6012
- Cool white, neutral white, and warm white color temperature
- Open cavity / no lens to trap dirt or insects
- Simple installation
- Virtually maintenance free
- Limited 5-year warranty



LUMINAIRE ORDERING INFORMATION

TYPICAL ORDER EXAMPLE SLI24 LED HO NW UE ALOS EM

Prefix	Light Source	Drive Current	Color Temperature	Line Voltage	Controls	Options
SLI22 - (2x2) SLI24 - (2x4)	LED	SS - Super Saver HO - High Output	CW - Cool White (5000K) NW - Neutral White (4000K) WW - Warm White (3500K)	UE - Universal Input Voltage (120-277V) 347 - 347V ¹	Blank (none) ALC - AirLink™ Controller ALOS - AirLink™ Controller w/ Occupancy Sensor ALVS - AirLink™ Controller w/ Vacancy Sensor	EM - Emergency Battery FC1 - 6' 3/8" (3) #18 Leads (For Use In Non-Dimming Applications) FC15D - 6' 3/8" (5) #18 Leads (For Use In Dimming Applications) SD50 - Step Dimming to 50% L3D - Lutron Hi-lume 1% LDE1 - Lutron Hi-lume 1% (with Soft-On, Fade-to-Black) LDE5 - Lutron 5-Series