

# LED SIDE LIGHT RECESSED TROFFER (SLI)



## PRODUCT HIGHLIGHTS

- Long life, high brightness LEDs virtually eliminate maintenance.
- RoHS compliant, recyclable “green” design contains no mercury or other hazardous materials.
- Cooler running electronic components allow for improved lumen performance.
- Indirect unit with balanced illumination from sides of fixture and superior, low angle brightness control.
- Available with AirLink™ wireless controls for maximum energy savings.

**EXPECTED LIFE** - Projected life of at least 60,000 hours. Contact factory for TM-21 detail.

**LEDs** - Use of closely spaced medium-power, high brightness chips minimizes pixelation and provides uniform luminance. Available in Cool White (5000K), Neutral White (4000K) and Warm White (3500K) color temperatures. CRI  $\geq$  80. LM\_80 reports available.

**HOUSING** - Formed code-gauge steel housing, painted after fabrication. Integral NEC-compliant earthquake clips are standard.

**FINISH** - All metal parts are painted after fabrication following treatment with phosphate rust inhibitor. Finish coating of housing reflecting surfaces is with high-reflectance (minimum 92%) matte white polyester powder.

**INSTALLATION** - Unit simply lifts through grid ceiling and rests on T-bars. Wiring access/strain relief plate attaches with one screw, allowing connections to be made from below the ceiling.

**ELECTRICAL** - Universal voltage (120-277 Vac) Input 50/60 Hz. Power factor  $>$  0.95, THD  $<$  20%

**DRIVER** - High-performance isolated driver features over-voltage, under-voltage, short-circuit and over temperature protection. Class A sound rating. 0-10 volt dimming (1% - 100%) standard.

**AirLink™** - LSI AirLink™ controls featuring Lutron® Clear Connect™ makes each luminaire controllable, creating a wireless communication with other AirLink™ control devices such as dimmers, switches, occupancy sensors and photocontrols. The integrated sensor is both a passive infrared motion detector and photocell. The photocell provides a simple out-of-the-box daylight harvesting solution. The motion detector uses exclusive Lutron XCT™ technology which provides fine motion detection and 360° sensor field-of-range.


**OPERATING TEMPERATURE** -  $-40^{\circ}\text{C}$  -  $+40^{\circ}\text{C}$  ( $-40^{\circ}\text{F}$  -  $+104^{\circ}\text{F}$ )

**WARRANTY** - Limited 5-year warranty.

**PHOTOMETRICS** - Please visit our web site at [www.lsi-industries.com](http://www.lsi-industries.com) for detailed photometric data.

**LISTING** - Listed to UL 1598 and UL 8750. Suitable For Damp Locations. IC Rated.

## DIMENSIONS




END VIEW

2 x 2 Length = 23-13/16" (605mm)  
2 x 4 Length = 47-13/16" (1214mm)

LIGHT OUTPUT - SLI								
	SS - Super Saver			HO - High Output			Watts	
	WW	NW	CW	WW	NW	CW	SS	HO
SLI22 (2X2)	2569	2408	2991	2973	3083	3517	29	36
SLI24 (2X4)	4004	4184	4797	5035	5269	6012	45	59

LED Chips are frequently updated therefore values may increase.

## AirLink™ ALOS AND ALVS COVERAGE PATTERN



This product, or selected versions of this product, meet the standards listed below. Please consult factory for your specific requirements.



Project Name \_\_\_\_\_ Fixture Type \_\_\_\_\_  
Catalog # \_\_\_\_\_

09/07/22  
© 2022  
LSI INDUSTRIES INC.

# LED SIDE LIGHT RECESSED TROFFER (SLI)

## LUMINAIRE ORDERING INFORMATION

TYPICAL ORDER EXAMPLE: **SLI24 LED HO NW UE ALOS EM**

Prefix	Light Source	Drive Current	Color Temperature	Line Voltage	Controls	Options (factory installed)
SLI22 - (2x2) SLI24 - (2x4)	LED	SS - Super Saver HO - High Output	CW - Cool White (5000K)  NW - Neutral White (4000K)  WW - Warm White (3500K)	UE - Universal Voltage (120-277V)  347-347V <sup>1</sup>	Blank (none)  ALC - AirLink™ Controller  ALOS - AirLink™ Controller w/ Occupancy Sensor  ALVS - AirLink™ Controller w/ Vacancy Sensor	EM - Emergency Battery FC1 - 6' 3/8" (3) #18 Leads (For Use In Non-Dimming Applications) FC15D - 6' 3/8" (5) #18 Leads (For Use In Dimming Applications) SD50 - Step Dimming to 50% LDE1 - Lutron Hi-Lume 1% (with Soft-On, Fade-to-Black) LDE5 - Lutron 5-Series FC16DEM - 6' 3/8" (6) #18 Leads (For use in Dimming & EM Applications)

### ACCESSORY ORDERING INFORMATION (Accessories are field installed)

Description	Order Number
Flange Kit - 2x4	FK24
Flange Kit - 2x2	FK22

### AIRLINK™ CONTROL ACCESSORIES Order as separate catalog number. Visit <http://www.lsi-airlink.com> for complete listing of AirLink™ controls.

Wireless switches	Catalog number	Part Number	Wireless Occupancy Sensors	Model number	Part Number
On/Off & Raise Lower	ALWS 3B-(color)-KIT <sup>2</sup>	624103CLR <sup>2</sup>	Wireless 360° 400 ft <sup>2</sup> , Ceiling Mount	ALCM-W-OS	624094
			Wireless 180° 3000 ft <sup>2</sup> , Wall Mount	ALWM-W-OS	632617
Wireless Photocell controls	Catalog number	Part Number	Wireless 90° 2500 ft <sup>2</sup> , Corner Mount <td>ALCR-W-OS</td> <td>624096</td>	ALCR-W-OS	624096
On/Off & Dimming	ALCM-W-PC	624090	Wireless, Hallway 150 ft Length	ALHW-W-OS	632620
<b>Commission Laser Kit</b> (See Laser warnings)	AL-CLK	634574			

### FOOTNOTES:

1 - Not available with AirLink

2 - Available colors are White, Ivory and Light Almond (WHT, IV, LA)

3 - Custom lumen and CCT packages available upon request. Contact factory for details. Values are within industry standard tolerances and not DLC listed.

### LASER Warnings:

Warning: Eye injury and/or blindness hazard; avoid direct eye exposure to laser beam.

- Use of laser pointer is NOT recommended for use with AirLink products located near reflective surfaces.
- Do NOT aim or shine laser pointers at any person, pet, vehicle, or aircraft directly, or through reflection by mirrors or other shiny surfaces.
- Do NOT view the laser beam through binoculars, magnifying glass, or other optical devices.
- Do NOT allow children to use laser pointers.
- Read and follow the laser pointer manufacturer's instructions on safe use. In the event of injury, get medical attention immediately.



Project Name \_\_\_\_\_ Fixture Type \_\_\_\_\_

Catalog # \_\_\_\_\_

09/07/22

© 2022  
LSI INDUSTRIES INC.