



Catalog #: \_\_\_\_\_ Project: \_\_\_\_\_

Prepared By: \_\_\_\_\_ Date: \_\_\_\_\_ Type: \_\_\_\_\_

# EWC

## Wet Location Exit Sign Combo



### FEATURES & SPECIFICATIONS

#### Construction

- Injection-molded UL 94 5VA flame retardant, high temperature, impact resistant polycarbonate housing
- One piece molded weatherproof silicone gasket
- All configurations include field-selectable directional chevrons
- Includes two face plates and a back plate
- Standard finish: White

#### Optical System

- Illuminated by long-life, high intensity red or green LEDs
- Fully-illuminated 6" characters with 3/4" stroke
- Adjustable 1.17 Watt LED lamp heads

#### Electrical

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz
- Brownout circuit monitor
- Short circuit and overcharge protection
- Test button to provide manual verification of the transfer circuit and emergency lamps
- RC option compatible with one SRL or CRL

#### Battery

- Maintenance free NiMH Battery
- Operating Temperatures 10°C to 40°C (50°F to 104°F)

#### Installation

- Quick connect for effortless installation
- Includes mounting bracket for wall and end mount

#### Warranty

- 5 year warranty on all electronics and housing
- Separate 5 year pro-rated warranty on the battery

#### Listings

- UL 924 Wet Location
- NFPA 101
- NEC
- CEC
- UL Listed 90 minute emergency run time, 24 hour recharge time

### ORDERING GUIDE

TYPICAL ORDER EXAMPLE: **EWC R WH RC**

Prefix	Letter Color	Housing Color	Options
EWC - Wet Location Exit Combo	R - Red G - Green	WH - White	RC <sup>1</sup> - 1W Remote Capacity PGB6 - Poly Guard Back Mount

#### FOOTNOTES:

1 - RC option compatible with one SRL or CRL

### PRODUCT DIMENSIONS

