



Catalog #: \_\_\_\_\_ Project: \_\_\_\_\_ Type: \_\_\_\_\_

Prepared By: \_\_\_\_\_ Date: \_\_\_\_\_

# AirLink™ Time Keeper w/ Long Range Extender (ALBTK 120 LRE 120V INT)

Time Keeper with Long Range Extender



Suitable For Interior

## OVERVIEW

Mounting	120v Receptacle
Coverage Range (ft)	approx 350' radius
Coverage Area (ft <sup>2</sup> )	384k sq ft

## QUICK LINKS

## FEATURES & SPECIFICATIONS

### Description

- The AirLink Blue time keeper with long range extender provides NTP time server sync with the ability to extend the signal range of the system through 350' from the mounting location.
- Strategically placed within the project site location will improve distance and quality of the Bluetooth wireless signal.

### Construction

- Surface Mounted Non-Metallic Enclosure
- Rated for indoor installations

### Electrical

- Line Voltage Input 120 VAC

### Controls

- Multiple fixtures can be grouped and controlled by scheduled time events.
- Max Bluetooth range is 350' line of sight and highly dependent on the integration of fixtures, surrounding environment. It is recommended to conduct testing for range accuracy

### Installation

- The time keeper can be wall or ceiling mount as close to the geometrical center of the lighting network as possible. Mount indoors on an outside wall near a window for maximum range.
- The long range extender is designed to be surface mounted to a wall structure.
- Operating temperature range of -30°C to +70°C (-22°F to 158°F)

### Warranty

- LSI luminaires carry a 5-year limited warranty. Refer to <https://www.lsicorp.com/resources/terms-conditions-warranty/> for more information.

### Listings

- FCC
- Bluetooth
- For technical support contact us at [controls.support@lsicorp.com](mailto:controls.support@lsicorp.com) or call (800) 436-7800, option 4

## ORDERING GUIDE

### TYPICAL ORDER EXAMPLE: ALBTK 120 LRE 120V INT

Prefix	Description	Part Number
ALBTK 120 LRE 120V INT	AirLink Blue time keeper with long range extender	842539



Need more information?  
Click here for our glossary

Have additional questions?  
Call us at (800) 436-7800

