



Internal Slip Fitter (BKS *ISF)

Pole Top Slip Fitter



FEATURES & SPECIFICATIONS

- Allows integration of LSI Luminaires and quick mount brackets to open top round poles with the following wall thicknesses:
 - 11 ga., 10 ga., or 7 ga. Wall thickness (round straight steel poles)
 - 0.125", 0.156", or 0.188" Wall thickness (round straight aluminum poles)
- Double welded steel plate to hold the tenon.
- Bolt through secures tenon internally.
- Adaptors are painted with LSI - DuraGrip® Paint.
- Assembled Mounting hardware included.

TYPICAL ORDER EXAMPLE: BKS ISF10 4RP BLK

Prefix	Length of Tube	Size of Pole	Finish
BKS	ISF10	4RP - 4 Inch Round 5RP - 5 Inch Round	BRZ - Bronze BLK - Black MSV - Metallic Silver GPT - Graphite WHT - White SVG - Satin Verde Green PLP - Platinum Plus ¹ Custom Colors Available. Please contact factory.



Need more information?
[Click here for our glossary](#)

Have additional questions?
Call us at (800) 436-7800



COMPATIBLE FIXTURES



ACCESSORY ORDERING INFORMATION

Part Number	Description
925375CLR	4 Inch Round Internal Slip Fitter
925610CLR	5 Inch Round Internal Slip Fitter

PRODUCT DIMENSIONS

