



CREX

Chicago Rated LED Exit Sign



OVERVIEW

Mounting Configurations	Ceiling, End, Wall & Pendant
Character Style	6" Characters with 3/4" Stroke
Input VAC (Hz)	120-277 (50/60)
Battery (min)	LiFePO4 Battery (90)
Sign Face Material	Heat-Tempered Glass

QUICK LINKS

FEATURES & SPECIFICATIONS

Construction

- 20 Gauge steel with a white powder coated finish.
- Glass panels are heat-tempered and impact- and scratch-resistant with red silkscreened lettering on white finish.
- Units come standard with the Single Face EXIT Less Arrows sign face panel.
- A multitude of replacement sign face accessories are available to select from, including EXIT and STAIRS configurations with directional arrows.

Optical System

- Legend illuminated by long-life, high intensity white LEDs.
- 6" characters with 3/4" stroke.

Battery

- Maintenance-free LiFePO4 battery.
- 5°C to 45°C (41°F to 113°F)

Electrical

- Universal Input Voltage - 120 to 277VAC at 50/60Hz.
- Low voltage disconnect eliminates deep discharge.
- Brownout protection.
- Test button to provide manual verification of the transfer circuit.
- Optional Remote Capacity - 9.6V, 3W. Supports one additional double lamp head or two single lamp heads.

Installation

- Includes all necessary hardware for ceiling, end or wall mounting, knockouts are included on top for pendant mount.

Warranty

- LSI luminaires carry a 5-year limited warranty. Refer to <https://www.lsicorp.com/resources/terms-conditions/warranty/> for more information.

Listings

- UL 924 Damp Location.
- Meets City of Chicago egress requirements.
- Meets or exceeds NFPA 101 and NEC.
- UL Listed 90 minute emergency run time, 24 hour recharge time.



CREX Chicago Rated LED Exit Sign

Type : _____

 **Have questions?** Call us at (800) 436-7800

ORDERING GUIDE

TYPICAL ORDER EXAMPLE: CREX R WB WH R

Prefix	Sign Face ^{1,2}	Battery	Housing Color	Options ²
CREX - Chicago Rated LED Exit Sign	R - Red Characters (Single Face EXIT Less Arrows)	LB - Less Battery (AC Only) WB - With Battery (LiFeP04 Battery)	WH - White	Blank - None R - 3W Remote Capacity ³

**Need more information?**
[Click here for our glossary](#)

Have additional questions?
Call us at (800) 436-7800

ACCESSORY ORDERING INFORMATION

Category	Part Number	Description
Replacement Sign Face Panels	916325	Single Face EXIT Less Arrows
	916326	Single Face EXIT Left Arrow ◀
	916327	Single Face EXIT Right Arrow ▶
	916328	Single Face EXIT Dual Arrows ◀ ▶
	916329	Single Face STAIRS Less Arrows
	916330	Single Face STAIRS Left Arrow ◀
	916331	Single Face STAIRS Right Arrow ▶
	916332	Dual Face EXIT Less Arrows
	916333	Dual Face EXIT with Dual Arrows ◀ ▶
	916334	Dual Face EXIT with Single Arrows ◀ or ▶
	916335	Dual Face STAIRS Less Arrows
	916336	Dual Face STAIRS with Single Arrows ◀ or ▶

- 1 All panels supplied with red letters on a white background.
- 2 Units come standard with the Single Face EXIT Less Arrows sign face panel. Replacement sign face panels are available as accessories and ship separately.
- 3 WB Only; Compatible with RRL Round Remote Lamp.

PRODUCT DIMENSIONS

