



Catalog #: _____ Project: _____

Prepared By: _____ Date: _____ Type: _____

LUNA

LSI Drum Pendant



FEATURES & SPECIFICATIONS

Diffuser

- The drum features a high quality UV stabilized white acrylic outer shell, with your choice of fabric bonded to its exterior sidewall. The base (bottom) of the drum is constructed with high transmission white acrylic. The fixture can be cleaned with a damp cloth and mild detergent if needed. See accessories section for Top Cover Set.

Housing

- Formed, cold rolled steel design, finished in a high reflectance powder coat white.

LED Performance - 3500K Standard

- 120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs Amperage rated @ 110V input

- Operating ambient temperature: -20°C / -4°F - 40°C / 104°F
- Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

Mounting

- Directly to j-box (by others). Mounting hardware included.

Suspension System

The 2600 Series is available in multiple colors and four suspension methods:

- CC1 - Cord & Single Cable: Both the power cord and aircraft cable can be trimmed in the field. See optional ordering code CE1 and CE2 for
- extended 10' and 20' drops. Recommended for pendants up to 36"Ø only.

- CC3 - Cord & Three Cable: Both the power cord and aircraft cables can be trimmed in the field. See optional ordering code CE1 and CE2 for extended 10' and 20' drops.
- SCM - Stem & Cable Mount: Steel stem in your choice of finish with three aircraft cables. The standard overall height (OAH) can be extended with additional stem sections in 1' and 2' intervals - see accessories section.
- SSM - Single Stem Mount: Traditional pendant style. Steel stem in your choice of finish. The standard overall height (OAH) can be extended with additional stem sections in 1' and 2' intervals - see accessories section. Recommended for pendants up to 36"Ø only.





LUNA LSI Drum Pendant

ORDERING GUIDE

[Back to Quick Links](#)TYPICAL ORDER EXAMPLE: **LUNA 36 FWL 45L UNV DIM 840 ST12 W N**

Family	Size	Outer Material & Diffuser	Lumen Options	Voltage	Dimming	CCT & CRI	Suspension	Finish	Options
LUNA	36 - 36" 48 - 48"	FWL - Fabric Diffuse White Linen	45L - 4500lm	UNV - 120-277V	DIM	840 - 4000K 80 CRI	SC12 - Stem & Cable 144" White ST12 - Single Stem 144" White	W - White	N - None D - Dust Cover

Accessory Ordering Information

Description
JNR - Joiner 3" diameter

PRODUCT DIMENSIONS

