Design Selector - Pickleball

Single Court (30'x60')
(2) ZMM-48L-2M-40K8 Fixtures
20' Mtg.Ht.
Residential 30fc Average





Luminaire Schedule							
Symbol	Qty	Description	Lum. Lumens	Lum. Watts	LER	Total Watts	LLF
	2	ZMM-48L-2M-40K8	42359	306	138	612	0.940

Calculation Summary							
Label	CalcType	Units	Avg	Max	Min	Avg/Min	Max/Min
01_PPA	Illuminance	Fc	31	43	22	1.4	2.0

Luminaire Location Summary					
LumNo	X	Y	Z	Orient	Tilt
1	32.575	30	20	180	0
2	-2.486	30	20	0	0

Based on the information provided, all dimensions and luminaire locations shown represent recommended positions. The engineer and/or architect must determine the applicability of the layout to existing or future field conditions. This lighting plan represents illumination levels calculated from laboratory data taken under controlled conditions in accordance with The Illuminating Engineering Society (IES) approved methods. Actual performance of any manufacturer's luminaires may vary due to changes in electrical voltage, tolerance in lamps/LED's and other variable field conditions.

Calculations do not include obstructions such as buildings, curbs, landscaping, or any other architectural elements unless noted. Fixture nomenclature noted does not include mounting hardware or poles. This drawing is for photometric evaluation purposes only and should not be used as a construction document or as a final document for ordering product.

LSI Industries Inc. 10000 Alliance Road. Cincinnati, OH 45242 www.lsicorp.com