



Flood Lighting Brackets

Wall Mount and Bolt-on Brackets



FEATURES & SPECIFICATIONS

- Rugged steel bolt on flood light bracket.
- All tenons are standard 2 3/8"
- Bracket finished with LSI's DuraGrip polyester powder coat finishing process. The DuraGrip finish withstands extreme weather changes without cracking or peeling. Other standard LSI finishes available. Consult Factory.

COMPATIBLE FIXTURES



TYPICAL ORDER EXAMPLE: BKS FBO 5 BLK

Prefix	Bracket Type	Bracket Configuration	Finish
BOLT-ON BKS - Bracket Steel	FBO ¹ FWM	5 18 30	BRZ - Bronze BLK - Black MSV - Metallic Silver GPT - Graphite WHT - White SVG - Satin Verde Green PLP - Platinum Plus
		5S 18C	



Need more information?
[Click here for our glossary](#)

Have additional questions?
Call us at (800) 436-7800






Note: Standard slip-fitter fits 2-3/8" O.D. tenon (2.0 pipe tenon)



Catalog Number	EPA ²	Est. Weight (kg/lbs.)
BKS-FBO-5	0.1	2/5
BKS-FBO-18	0.6	6/14
BKS-FBO-30	1.0	13/29

PRODUCT DIMENSIONS

STEEL POLE BOLT-ON BRACKETS



STEEL WALL MOUNT BRACKETS



1 FBO brackets require pole preparation and must be ordered with "SF" or "DF" pole option. For use with Steel Poles only. Consult factory for bolt-on flood brackets for aluminum poles.

2 The bracket EPA should be added to the fixture EPA when selecting the proper pole.

