



Catalog # : _____ Project : _____

Prepared By : _____ Date : _____

AirLink™ Blue
Technology Partner **SILVAIR**

Control Module



The AirLink Blue control module provides multi-level control based on external motion and/or daylight sensor inputs. Controls 0-10 VDC LED drivers and is rated for cold and wet locations (-40°C to 85°C). Control parameters are adjustable via an iOS App. The addition of an AirLink Blue Time Keeper adds the ability to schedule multiple events based on time of day or Astronomical clock.

FEATURES & SPECIFICATIONS

Construction

- Bluetooth Mesh radio pairs with iOS applications for initial system setup and subsequent adjustments or changes.
- Housing is white polycarbonate
- Settings are stored and maintained in the event of a power failure

Electrical

- Class 2 device with a 0-10V configurable dimming output
- Operates on 12-24 VDC from either a 120-277V power pack or auxiliary output driver
- 12-24 VDC input voltage current consumption 100mA

Controls

Range (Module and antenna inside fixture)

- Phone to fixture 75 feet
- Fixture to fixture 100 feet

Installation

- Designed for installation on the interior of a luminaire housing.
- Rated for use in -22° F to 158°F (-30°C to 70°C) environments.

Warranty

- 5-year warranty.

Listings

- FCC
- Bluetooth
- UL

ORDERING GUIDE

Catalog Number	Description
ALBC	AirLink Blue Control Module

PRODUCT DIMENSIONS

