



Catalog # : _____ Project : _____

Prepared By : _____ Date : _____

AWL

All-Weather Wallpack - Low Profile



OVERVIEW	
Lumen Range	1500
CCT	4000K
Wattage	15
Efficacy (LPW)	100
Weight lbs (kg)	3.7 lbs (EP model 4.5 lbs.)

FEATURES & SPECIFICATIONS

Construction

- Die-cast aluminum housing
- Available in Bronze, White, Black, and Silver

Optical

- UV-resistant, high-impact polycarbonate lens
- Minimum CRI of 70

Electrical

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz
- Emergency Package (EP) option draws and additional 17W and includes self-test/self-diagnostic and a heater for cold weather operation to -25°C (-13°F)
- Standard photocontrol sensor for use in dusk to dawn applications that can be disabled

to be used as and always on or switchable fixture.

- Optional PIR motion sensor (PIR) with up to 10' of detection and operational dusk to dawn. The light will activate when motion is detected in AC mode only and turn off after two minutes of inactivity.

Battery

- Maintenance-free NiCad Battery
- Operating temperatures: -25°C to 50°C (-13°F to 122°F)

Installation

- Universal pattern backplate provides 3" or 4" J-box mounting pattern with keyhole slots
- Can be surface mounted using the 1/2" conduit entry point at top of housing

Warranty

- 5 year warranty on all electronics and housing

Listings

- UL 924
- cULus Listed for Wet Locations
- IP65 rated
- State of California Title 24
- NFPA 101
- NFPA 70
- NEC
- UL Listed 90 minute emergency run time, 24 hour recharge time

ORDERING GUIDE

TYPICAL ORDER EXAMPLE: **AWL BR EP**

Prefix	Housing Color	Controls
AWL - All-Weather Wallpack Low Profile	BR - Bronze WH - White BK - Black SL - Silver	EP ¹ - Emergency Package PIR ² - PIR motion sensor

1 - EP option includes self-test/self-diagnostic and a heater for cold weather operation to -25°C (-13°F)

2 - PIR option adds a PIR motion sensor and removes photocontrol

PRODUCT DIMENSIONS

