



Catalog #: _____ Project: _____

Prepared By: _____ Date: _____ Type: _____

EWV

Wet Location - Vandal Resistant Exit



IP66



FEATURES & SPECIFICATIONS

Construction

- Heavy duty cast aluminum housing with impact-resistant polycarbonate shield
- Tamper resistant hardware standard
- All configurations include field-selectable directional chevrons
- Standard finish: White and Black
- Buy American Act (BAA) compliant with US option

Optical System

- Illuminated by long-life, high intensity red or green LEDs
- Fully-illuminated 6" characters with 3/4" stroke

Electrical

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz

- Brownout circuit monitor
- Solid-state transfer detects loss of line voltage and automatically switches to emergency mode
- Test button to provide manual verification of the transfer circuit and emergency lamps

Battery

- Maintenance free NiCad Battery (WB only)
- Operating Temperatures 10°C to 40°C (50°F to 104°F)
- Optional internal battery heater for cold locations down to -20°C (-4°F) (BH_)
- Optional extended 120 minute run time battery (XNB)

Installation

- Includes mounting bracket for wall end and ceiling mount applications

Warranty

- 5 year warranty on all electronics and housing
- Separate 5 year pro-rated warranty on the battery

Listings

- UL 924
- NFPA 101
- NEC
- CEC
- Wet Location Rated
- UL Listed 90 minute emergency run time, 24 hour recharge time
- IP66 Rated
- CSA Listed
- NSF Standard 2 Certified

ORDERING GUIDE

TYPICAL ORDER EXAMPLE: **EWV R 1F WB WH US**

Prefix	Letter Color	# of Faces	Battery	Housing Color	Options
EWV - Wet Location - Vandal Resistant Exit	R - Red G - Green	1F - Single Face 2F - Dual Face	LB - Less Battery (AC Only) WB - With Battery	WH - White BK - Black	BH 120 - Battery Heater (120VAC) BH277 - Battery Heater (277 VAC) XNB - Extended 120 minute battery run time US - Meets Buy American Requirements (BAA) 2CI1 ¹ - 2 Circuit Input (120VAC) 2CI7 ¹ - 2 Circuit Input (277VAC)

FOOTNOTES:

1 - LB option for use with generator or inverter applications only.

PRODUCT DIMENSIONS

