



Catalog # : _____ Project : _____

Prepared By : _____ Date : _____

HEL

High Performance Emergency Light



damp location



FEATURES & SPECIFICATIONS

Construction

- Injection-molded UL 5VA flame retardant, thermoplastic housing
- Standard finish: White and Black

Optical

- HP1 delivers 520 lumens with dual adjustable 2.7W lamps
- HP2 delivers 1100 lumens with dual adjustable 5.4W lamps

Electrical

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz
- Test button to provide manual verification of the transfer circuit and emergency lamps

- RC option compatible with SRL, PORL, and RRLS remote heads up to 5.4W

Battery

- Maintenance free Lithium Phosphate Battery
- Operating Temperature 0°C to 40°C (32°F to 104°F)
- 90 minute emergency run time, 24 - 48 hour recharge time

Installation

- Universal J-box mounting pattern with keyhole slots

Warranty

- 5 year warranty on all electronics and housing.

- Separate 3 year pro-rated warranty on the battery.

Listings

- UL 924
- cUL
- NPFA 101
- NEC
- California Energy Commission (CEC) compliant
- Suitable for Damp Locations

Specifications and dimensions subject to change without notice.

ORDERING GUIDE

TYPICAL ORDER EXAMPLE:

HEL HP2 WH SD2

Prefix	Output	Housing Color	Options
HEL - High Performance Emergency Light	HP1 - Two 2.7W LED Lamps HP2 - Two 5.4W LED Lamps	WH - White BK - Black	SD2 - Self Test/Self Diagnostic RC1 - 5.4W Remote Capacity WGB1 - Back Mount Wire Guard

1 - RC option not available with HP2 selection

PRODUCT DIMENSIONS

