



Pole Comparison Chart

						
	4SQU	5SQU	6SQU	4RPU	5RPU	RTPU
Size	4" Square	5" Square	6" Square	4" Round	5" Round	Round Tapered
Gauge (thickness in inches)	11 / 7 (1/8" / 3/16")	11 / 7 (1/8" / 3/16")	7 (3/16")	10 (9/64")	11 / 7 (1/8" / 3/16")	11 / 7 (1/8" / 3/16")
Weight lbs./ft. (approx.)	7.5 / 10	9 / 12.5	15.4	6	7 / 10	see spec sheet
Standard Heights	12' - 26' / 14' - 30'	14' - 30' / 20' - 35'	24' - 39'	14' - 24'	16' - 26' / 18' - 30'	20' - 39'
Bolt Circle Range	11" - 12"	11" - 13"	11" - 14"	7" - 11"	7-1/2" - 13" / 8" - 13"	see spec sheet
Anchor Bolt Size	3/4" x 30"	3/4" x 30" / 1" x 36"	1" x 36"	3/4" x 30"	3/4" x 30" / 1" x 36"	1" x 36" / 1-1/4" x 42"
Shaft Minimum Yield Strength	50,000 psi	50,000 psi	50,000 psi	46,000 psi	46,000 psi	50,000 psi
Base Plate Minimum Yield Strength	36,000 psi	36,000 psi	36,000 psi	36,000 psi	36,000 psi	36,000 psi
Paint Colors	LSI Standard + Custom Colors	LSI Standard + Custom Colors	LSI Standard + Custom Colors	LSI Standard + Custom Colors	LSI Standard + Custom Colors	LSI Standard + Custom Colors
Paint Finishes	DuraGrip / DuraGrip+	DuraGrip / DuraGrip+	DuraGrip / DuraGrip+	DuraGrip / DuraGrip+	DuraGrip / DuraGrip+	DuraGrip / DuraGrip+
Listings / Compliance	BAA/TAA / UL	BAA/TAA / UL	BAA/TAA / UL	BAA/TAA / UL	BAA/TAA / UL	BAA/TAA / UL
Pricing	\$	\$\$	\$\$\$	\$	\$\$	\$\$\$

SELL.1102.B.0921

Visit us online at www.liscorp.com for more information.

LSI Industries Inc. 10000 Alliance Rd. Cincinnati, OH 45242 · www.liscorp.com · (800) 436-7800 · ©2021 LSI Industries Inc. All Rights Reserved.