



SMA - Commercial Area Medium Light

SMA PERFORMANCE TABLE

<u>Catalog Number</u>	<u>Delivered Lumens</u>	<u>Watts</u>	<u>Efficiency</u>	<u>BUG</u>
SMA-LED-28L-ACR-3-UNV-40	28,344	200	142	B4-U0-G4
SMA-LED-28L-ACR-3-UNV-50	28,038	200	140	B4-U0-G4
SMA-LED-28L-ACR-5W-UNV-40	28,392	200	142	B4-U0-G3
SMA-LED-28L-ACR-5W-UNV-50	28,085	200	140	B4-U0-G3
SMA-LED-28L-ACR-FT-40-UNV-IHS	17,050	200	85	B3-U0-G2
SMA-LED-28L-ACR-FT-50-UNV-IHS	16,866	200	84	B3-U0-G2
SMA-LED-28L-ACR-FT-UNV-40	27,547	200	138	B4-U0-G3
SMA-LED-28L-ACR-FT-UNV-50	27,250	200	136	B3-U0-G3
SMA-LED-42L-ACR-3-UNV-40	41,403	296	140	B4-U0-G4
SMA-LED-42L-ACR-3-UNV-50	40,955	296	138	B4-U0-G4
SMA-LED-42L-ACR-5W-UNV-40	41,473	296	140	B5-U0-G3
SMA-LED-42L-ACR-5W-UNV-50	41,024	296	139	B5-U0-G3
SMA-LED-42L-ACR-FT-40-UNV-IHS	24,907	296	84	B3-U0-G3
SMA-LED-42L-ACR-FT-50-UNV-IHS	24,638	296	83	B3-U0-G3
SMA-LED-42L-ACR-FT-UNV-40	40,238	296	136	B4-U0-G4
SMA-LED-42L-ACR-FT-UNV-50	39,803	296	134	B4-U0-G4



SMA - Commercial Area Medium Light

SMA - FLOOD DISTRIBUTIONS PERFORMANCE TABLE

<u>Catalog Number</u>	<u>Delivered Lumens</u>	<u>Watts</u>	<u>Efficiency</u>	<u>Nema Type (H x V)</u>	<u>Field (H x V)</u>	<u>Beam (H x V)</u>	<u>Max Cd</u>
SMA-LED-28L-ACR-M-UNV-40.ies	29,154	200	146	4 x 4	67.3 x 63.1	56.8 x 49.3	30,688
SMA-LED-28L-ACR-M-UNV-50.ies	28,834	200	144	4 x 4	67.3 x 63.1	56.8 x 49.3	30,351
SMA-LED-28L-ACR-W-UNV-40.ies	27,312	200	137	6 x 6	121.9 x 120.4	100.6 x 99.8	12,280
SMA-LED-28L-ACR-W-UNV-50.ies	27,010	200	135	6 x 6	121.9 x 120.4	100.6 x 99.8	12,144
SMA-LED-42L-ACR-M-UNV-40.ies	42,595	296	144	4 x 4	67.2 x 63.1	56.8 x 49.3	44,837
SMA-LED-42L-ACR-M-UNV-50.ies	42,127	296	142	4 x 4	67.2 x 63.1	56.8 x 49.3	44,344
SMA-LED-42L-ACR-W-UNV-40.ies	39,903	296	135	6 x 6	121.9 x 120.4	100.6 x 99.8	17,941
SMA-LED-42L-ACR-W-UNV-50.ies	39,643	296	134	6 x 6	121.9 x 120.4	100.6 x 99.8	17,824