



IES INDOOR REPORT
PHOTOMETRIC FILENAME : ASC22-LED-40L-DIM5-40.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST]LED-11084
[TESTLAB]LSI INDUSTRIES, INC
[ISSUE DATE]07/26/19
[TEST DATE]05/20/19
[MANUFACTURER]LSI INDUSTRIES, INC
[LUMEN CATEGORY]ASC22-LED-40L-DIM5-40
[ABSOLUTE]NOTE: DATA SHOWN IS ABSOLUTE FOR THE SAMPLE PROVIDED.
[OTHER]TEST PROCEDURE: IESNA LM-79-08
[SEARCH_SOURCE TYPE] LED
[SEARCH_APPLICATION] Indoor

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	4026
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	132
Total Luminaire Watts	30.5
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.30
Spacing Criterion (90-270)	1.42
Spacing Criterion (Diagonal)	1.48
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	2.00 ft
Luminous Width (90-270)	2.00 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	3239	3559	3890
55	3094	3600	4111
65	2856	3639	4040
75	2451	3272	3334
85	1573	1912	2468

IES INDOOR REPORT
PHOTOMETRIC FILENAME : ASC22-LED-40L-DIM5-40.IES

CANDELA TABULATION

	<u>0.0</u>	<u>22.5</u>	<u>45.0</u>	<u>67.5</u>	<u>90.0</u>
0.0	1239	1239	1239	1239	1239
2.5	1237	1238	1242	1245	1244
5.0	1235	1237	1242	1245	1245
7.5	1238	1238	1241	1244	1246
10.0	1229	1236	1241	1242	1243
12.5	1220	1224	1239	1239	1241
15.0	1209	1214	1225	1234	1237
17.5	1199	1203	1215	1231	1231
20.0	1182	1193	1203	1225	1223
22.5	1162	1170	1189	1210	1214
25.0	1140	1149	1174	1193	1202
27.5	1113	1125	1152	1177	1188
30.0	1081	1097	1129	1159	1172
32.5	1049	1066	1104	1139	1154
35.0	1014	1033	1076	1116	1133
37.5	976	997	1044	1091	1109
40.0	937	959	1010	1062	1084
42.5	895	919	974	1032	1054
45.0	852	877	936	1000	1023
47.5	807	834	896	964	990
50.0	760	788	855	928	956
52.5	712	740	812	889	919
55.0	660	691	768	846	877
57.5	607	643	720	802	829
60.0	555	592	674	751	774
62.5	503	542	625	688	708
65.0	449	491	572	620	635
67.5	396	440	515	549	560
70.0	343	389	451	472	481
72.5	290	337	384	394	400
75.0	236	282	315	316	321
77.5	182	229	240	240	242
80.0	135	171	171	163	172
82.5	91	115	106	117	131
85.0	51	60	62	77	80
87.5	20	20	21	14	13
90.0	0	0	0	0	0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : ASC22-LED-40L-DIM5-40.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	464.86	N.A.	11.50
0-30	1005.25	N.A.	25.00
0-40	1677.56	N.A.	41.70
0-60	3087.21	N.A.	76.70
0-80	3949.94	N.A.	98.10
0-90	4025.7	N.A.	100.00
10-90	3907.27	N.A.	97.10
20-40	1212.69	N.A.	30.10
20-50	1936.04	N.A.	48.10
40-70	1958.45	N.A.	48.60
60-80	862.73	N.A.	21.40
70-80	313.94	N.A.	7.80
80-90	75.75	N.A.	1.90
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	4025.7	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	118.42
10-20	346.44
20-30	540.39
30-40	672.30
40-50	723.35
50-60	686.31
60-70	548.79
70-80	313.94
80-90	75.75
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


IES INDOOR REPORT
PHOTOMETRIC FILENAME : ASC22-LED-40L-DIM5-40.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	108	103	99	95	106	101	97	93	97	93	90	93	90	88	89	87	85	83
2	98	90	82	76	95	88	81	76	84	79	74	81	76	72	78	74	70	68
3	89	78	70	63	87	77	69	62	74	67	61	71	65	60	68	63	59	57
4	81	69	60	53	79	68	59	52	65	58	52	63	56	51	60	55	50	48
5	75	61	52	45	72	60	51	45	58	50	44	56	49	44	54	48	43	41
6	69	55	46	39	67	54	45	39	52	44	39	50	44	38	49	43	38	36
7	64	50	41	34	62	49	40	34	47	40	34	46	39	34	44	38	33	31
8	59	45	37	31	57	45	36	30	43	36	30	42	35	30	41	34	30	28
9	55	41	33	27	54	41	33	27	40	32	27	39	32	27	38	31	27	25
10	52	38	30	25	50	38	30	25	37	29	25	36	29	24	35	29	24	22

POLAR GRAPH



Maximum Candela = 1246 Located At Horizontal Angle = 90, Vertical Angle = 7.5
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (7.5) (Through Max. Cd.)