



IES INDOOR REPORT

PHOTOMETRIC FILENAME : GA14-LED-SS-WW-P12.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST]LED-4683A
[TESTLAB]LSI INDUSTRIES, INC
[ISSUEDATE]3/216
[TESTDATE]11/11/13
[MANUFAC]LSI INDUSTRIES, INC
[_ABSOLUTE]NOTE: DATA SHOWN IS ABSOLUTE FOR THE SAMPLE PROVIDED.
[OTHER]SCALED FROM ORIGINAL TEST DATA
[OTHER]TEST PROCEDURE: IESNA LM-79-08
[_SEARCH_SOURCE]TYPE] LED
[_SEARCH_APPLICATION] Indoor
[LUMCAT]GA14-LED-SS-WW-P12

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	3147
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	109
Total Luminaire Watts	29
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.30
Spacing Criterion (90-270)	1.24
Spacing Criterion (Diagonal)	1.32
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	4.00 ft
Luminous Width (90-270)	1.00 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	3206	2968	2514
55	2545	2104	1669
65	1882	1402	1343
75	1494	1133	1470
85	1932	1825	2326

IES INDOOR REPORT
PHOTOMETRIC FILENAME : GA14-LED-SS-WW-P12.IES

CANDELA TABULATION

	<u>0.0</u>	<u>22.5</u>	<u>45.0</u>	<u>67.5</u>	<u>90.0</u>
0.0	1342.12	1342.12	1342.12	1342.12	1342.12
2.5	1378.08	1356.04	1340.96	1328.20	1318.92
5.0	1375.76	1352.56	1338.64	1325.88	1314.28
7.5	1371.12	1350.24	1334.00	1321.24	1309.64
10.0	1364.16	1342.12	1327.04	1313.12	1301.52
12.5	1354.88	1331.68	1315.44	1300.36	1291.08
15.0	1340.96	1318.92	1302.68	1286.44	1276.00
17.5	1324.72	1303.84	1286.44	1270.20	1259.76
20.0	1306.16	1284.12	1266.72	1249.32	1236.56
22.5	1279.48	1260.92	1243.52	1224.96	1214.52
25.0	1250.48	1233.08	1215.68	1197.12	1185.52
27.5	1218.00	1200.60	1183.20	1164.64	1155.36
30.0	1179.72	1163.48	1144.92	1127.52	1117.08
32.5	1136.80	1119.40	1100.84	1082.28	1071.84
35.0	1090.40	1071.84	1048.64	1026.60	1010.36
37.5	1035.88	1018.48	990.64	954.68	933.80
40.0	977.88	957.00	924.52	876.96	851.44
42.5	912.92	892.04	852.60	799.24	766.76
45.0	843.32	821.28	780.68	711.08	661.20
47.5	763.28	749.36	706.44	604.36	551.00
50.0	689.04	676.28	625.24	508.08	468.64
52.5	613.64	604.36	533.60	431.52	407.16
55.0	542.88	527.80	448.92	373.52	356.12
57.5	475.60	450.08	379.32	327.12	312.04
60.0	411.80	378.16	319.00	285.36	273.76
62.5	351.48	312.04	266.80	248.24	238.96
65.0	295.80	259.84	220.40	218.08	211.12
67.5	245.92	218.08	182.12	192.56	184.44
70.0	206.48	183.28	150.80	172.84	167.04
72.5	171.68	155.44	126.44	155.44	153.12
75.0	143.84	133.40	109.04	140.36	141.52
77.5	120.64	113.68	97.44	124.12	131.08
80.0	104.40	93.96	87.00	106.72	116.00
82.5	85.84	75.40	75.40	90.48	97.44
85.0	62.64	56.84	59.16	73.08	75.40
87.5	37.12	37.12	37.12	48.72	45.24
90.0	0.00	0.00	0.00	0.00	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : GA14-LED-SS-WW-P12.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	495.83	N.A.	15.80
0-30	1055.51	N.A.	33.50
0-40	1707.68	N.A.	54.30
0-60	2700.93	N.A.	85.80
0-80	3082.05	N.A.	97.90
0-90	3146.99	N.A.	100.00
10-90	3019.38	N.A.	95.90
20-40	1211.85	N.A.	38.50
20-50	1798.78	N.A.	57.20
40-70	1233.67	N.A.	39.20
60-80	381.12	N.A.	12.10
70-80	140.69	N.A.	4.50
80-90	64.94	N.A.	2.10
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	3146.99	N.A.	100.00

Total Luminaire Efficiency = N.A.%

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	127.61
10-20	368.22
20-30	559.68
30-40	652.17
40-50	586.93
50-60	406.31
60-70	240.42
70-80	140.69
80-90	64.94
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


IES INDOOR REPORT
PHOTOMETRIC FILENAME : GA14-LED-SS-WW-P12.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	110	105	101	98	107	103	100	96	99	96	93	95	93	90	91	90	88	86
2	101	93	87	82	98	91	86	81	88	83	79	85	81	77	82	79	76	74
3	93	83	76	70	90	82	75	69	79	73	68	76	71	67	73	69	66	64
4	86	75	66	60	83	73	66	60	71	64	59	69	63	58	66	61	57	55
5	79	67	59	53	77	66	58	52	64	57	52	62	56	51	60	55	51	49
6	73	61	53	47	72	60	52	46	58	51	46	57	50	46	55	50	45	43
7	68	56	47	42	67	55	47	41	53	46	41	52	46	41	51	45	41	39
8	64	51	43	37	62	50	43	37	49	42	37	48	41	37	47	41	37	35
9	60	47	39	34	58	46	39	34	45	38	34	44	38	33	43	37	33	31
10	56	43	36	31	55	43	36	31	42	35	31	41	35	31	40	34	30	29

POLAR GRAPH



Maximum Candela = 1378.08 Located At Horizontal Angle = 0, Vertical Angle = 2.5
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (2.5) (Through Max. Cd.)