



## IES INDOOR REPORT

PHOTOMETRIC FILENAME : IHB4-LED-18L-LL-50.IES

### DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] 3128

[TESTLAB] TUV SUD America

[ISSUEDATE] 04/19/21

[MANUFAC] LSI INDUSTRIES, INC

[LUMCAT] IHB4-LED-18L-LL-50

[OTHER] TEST PROCEDURE: IESNA LM-79-08

[ABSOLUTE] NOTE: DATA SHOWN IS ABSOLUTE FOR THE SAMPLE PROVIDED

[OTHER] SCALED FROM ORIGINAL TEST DATA

[SEARCH\_SOURCETYPE] LED

[SEARCH\_APPLICATION] Indoor

[SEARCH\_COLORTEMP] 5000

### CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	21403
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	138
Total Luminaire Watts	155.03
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.28
Spacing Criterion (90-270)	1.32
Spacing Criterion (Diagonal)	1.44
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	4.00 ft
Luminous Width (90-270)	0.60 ft
Luminous Height	0.00 ft



### LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	31610	32615	33298
55	30357	31483	32344
65	13454	28503	29957
75	11155	12024	24863
85	3779	6590	12571

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : IHB4-LED-18L-LL-50.IES**

**CANDELA TABULATION**

	<u>0.0</u>	<u>22.5</u>	<u>45.0</u>	<u>67.5</u>	<u>90.0</u>	<u>112.5</u>	<u>135.0</u>	<u>157.5</u>	<u>180.0</u>	<u>202.5</u>
<b>0.0</b>	7388.08	7388.08	7388.08	7388.08	7388.08	7388.08	7388.08	7388.08	7388.08	7388.08
<b>2.5</b>	7362.48	7381.15	7356.77	7378.72	7398.23	7388.18	7380.27	7403.66	7388.63	7403.66
<b>5.0</b>	7339.18	7353.78	7331.76	7353.73	7384.53	7379.38	7370.55	7398.56	7385.98	7398.56
<b>7.5</b>	7368.49	7343.41	7298.54	7327.55	7355.23	7359.49	7350.32	7381.79	7369.40	7381.79
<b>10.0</b>	7295.60	7333.94	7273.63	7288.57	7314.83	7324.64	7322.39	7375.05	7365.02	7375.05
<b>12.5</b>	7207.86	7248.17	7244.20	7219.47	7260.81	7269.37	7291.17	7382.90	7368.54	7382.90
<b>15.0</b>	7102.75	7146.66	7156.43	7151.25	7191.23	7208.01	7293.78	7306.43	7299.36	7306.43
<b>17.5</b>	6984.91	7036.62	7056.41	7091.84	7115.15	7136.20	7205.04	7218.25	7208.55	7218.25
<b>20.0</b>	6865.50	6916.52	6932.23	7025.74	7022.74	7041.81	7113.13	7113.62	7109.49	7113.62
<b>22.5</b>	6725.34	6786.37	6812.26	6927.64	6912.57	6956.59	6997.94	7005.33	7002.48	7005.33
<b>25.0</b>	6585.48	6647.44	6675.96	6791.59	6793.02	6892.10	6878.23	6875.80	6889.76	6875.80
<b>27.5</b>	6435.86	6495.82	6527.65	6640.97	6655.05	6766.82	6743.12	6738.59	6761.43	6738.59
<b>30.0</b>	6262.54	6332.08	6362.43	6478.13	6505.40	6610.83	6591.12	6591.74	6624.20	6591.74
<b>32.5</b>	6090.48	6148.96	6186.12	6305.58	6340.45	6439.85	6423.58	6431.83	6483.49	6431.83
<b>35.0</b>	5898.98	5969.07	6002.44	6123.61	6165.18	6267.29	6248.40	6263.43	6323.08	6263.43
<b>37.5</b>	5693.61	5773.59	5806.18	5932.90	5950.41	6077.27	6059.49	6089.10	6155.89	6089.10
<b>40.0</b>	5478.60	5564.64	5594.03	5682.73	5714.67	5851.37	5860.67	5892.74	5982.32	5892.74
<b>42.5</b>	5245.20	5334.77	5377.23	5431.41	5498.45	5597.39	5653.69	5682.60	5775.83	5682.60
<b>45.0</b>	4988.33	5096.96	5146.97	5190.68	5254.69	5367.79	5435.94	5461.64	5554.18	5461.64
<b>47.5</b>	4735.61	4855.43	4893.14	4929.57	4985.78	5117.84	5205.51	5231.24	5318.40	5231.24
<b>50.0</b>	4468.88	4591.72	4609.96	4644.96	4722.93	4827.46	4920.07	4989.20	5069.46	4989.20
<b>52.5</b>	4171.11	4308.77	4324.06	4367.91	4429.12	4551.75	4641.98	4719.90	4818.21	4719.90
<b>55.0</b>	3885.91	4019.95	4030.12	4052.96	4140.36	4239.57	4374.70	4439.12	4550.94	4439.12
<b>57.5</b>	3257.88	3702.64	3742.44	3750.88	3825.90	3943.09	4088.87	4168.77	4280.43	4168.77
<b>60.0</b>	2174.80	3130.09	3443.26	3425.66	3501.25	3617.76	3808.61	3878.46	3992.92	3878.46
<b>62.5</b>	1454.07	2100.17	3123.86	3108.07	3166.22	3306.34	3488.79	3560.69	3629.54	3560.69
<b>65.0</b>	1268.96	1371.60	2688.38	2785.23	2825.47	2967.24	3157.15	2774.44	2294.67	2774.44
<b>67.5</b>	1097.12	1192.46	1862.75	2437.99	2479.90	2628.14	2809.11	1464.01	1489.75	1464.01
<b>70.0</b>	926.78	1030.58	1093.39	2104.19	2140.09	2283.07	2214.99	1266.65	1305.14	1266.65
<b>72.5</b>	787.66	866.03	858.10	1760.64	1776.28	1955.23	1087.98	1106.52	1149.93	1106.52
<b>75.0</b>	644.32	714.90	694.56	1390.88	1436.12	1613.51	884.32	945.17	989.85	945.17
<b>77.5</b>	494.43	567.57	542.28	827.38	1096.22	1288.17	713.52	782.42	835.96	782.42
<b>80.0</b>	339.68	408.00	407.53	404.45	787.15	620.45	556.70	630.56	684.90	630.56
<b>82.5</b>	151.99	234.61	272.94	254.02	493.16	331.77	419.75	477.17	527.01	477.17
<b>85.0</b>	73.51	103.57	128.19	146.75	244.51	203.08	282.61	320.11	367.26	320.11
<b>87.5</b>	3.76	27.77	47.37	62.67	67.78	115.45	140.79	149.25	184.75	149.25
<b>90.0</b>	0.48	7.81	14.47	22.12	6.86	41.34	60.52	70.66	93.38	70.66
<b>92.5</b>	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>95.0</b>	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>97.5</b>	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>100.0</b>	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>102.5</b>	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>105.0</b>	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>107.5</b>	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>110.0</b>	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>112.5</b>	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>115.0</b>	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>117.5</b>	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>120.0</b>	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>122.5</b>	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>125.0</b>	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>127.5</b>	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>130.0</b>	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>132.5</b>	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : IHB4-LED-18L-LL-50.IES**

**CANDELA TABULATION - (Cont.)**

135.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
137.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
140.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
142.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
145.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
147.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
152.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
155.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
157.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
160.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
162.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
165.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
167.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
170.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
172.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
175.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
177.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
180.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

**Vert. Angles**      **Horizontal Angles**

	<u>225.0</u>	<u>247.5</u>	<u>270.0</u>	<u>292.5</u>	<u>315.0</u>	<u>337.5</u>	<u>360.0</u>
0.0	7388.08	7388.08	7388.08	7388.08	7388.08	7388.08	7388.08
2.5	7380.27	7388.18	7398.23	7378.72	7356.77	7381.15	7362.48
5.0	7370.55	7379.38	7384.53	7353.73	7331.76	7353.78	7339.18
7.5	7350.32	7359.49	7355.23	7327.55	7298.54	7343.41	7368.49
10.0	7322.39	7324.64	7314.83	7288.57	7273.63	7333.94	7295.60
12.5	7291.17	7269.37	7260.81	7219.47	7244.20	7248.17	7207.86
15.0	7293.78	7208.01	7191.23	7151.25	7156.43	7146.66	7102.75
17.5	7205.04	7136.20	7115.15	7091.84	7056.41	7036.62	6984.91
20.0	7113.13	7041.81	7022.74	7025.74	6932.23	6916.52	6865.50
22.5	6997.94	6956.59	6912.57	6927.64	6812.26	6786.37	6725.34
25.0	6878.23	6892.10	6793.02	6791.59	6675.96	6647.44	6585.48
27.5	6743.12	6766.82	6655.05	6640.97	6527.65	6495.82	6435.86
30.0	6591.12	6610.83	6505.40	6478.13	6362.43	6332.08	6262.54
32.5	6423.58	6439.85	6340.45	6305.58	6186.12	6148.96	6090.48
35.0	6248.40	6267.29	6165.18	6123.61	6002.44	5969.07	5898.98
37.5	6059.49	6077.27	5950.41	5932.90	5806.18	5773.59	5693.61
40.0	5860.67	5851.37	5714.67	5682.73	5594.03	5564.64	5478.60
42.5	5653.69	5597.39	5498.45	5431.41	5377.23	5334.77	5245.20
45.0	5435.94	5367.79	5254.69	5190.68	5146.97	5096.96	4988.33
47.5	5205.51	5117.84	4985.78	4929.57	4893.14	4855.43	4735.61
50.0	4920.07	4827.46	4722.93	4644.96	4609.96	4591.72	4468.88
52.5	4641.98	4551.75	4429.12	4367.91	4324.06	4308.77	4171.11
55.0	4374.70	4239.57	4140.36	4052.96	4030.12	4019.95	3885.91
57.5	4088.87	3943.09	3825.90	3750.88	3742.44	3702.64	3257.88
60.0	3808.61	3617.76	3501.25	3425.66	3443.26	3130.09	2174.80
62.5	3488.79	3306.34	3166.22	3108.07	3123.86	2100.17	1454.07
65.0	3157.15	2967.24	2825.47	2785.23	2688.38	1371.60	1268.96
67.5	2809.11	2628.14	2479.90	2437.99	1862.75	1192.46	1097.12
70.0	2214.99	2283.07	2140.09	2104.19	1093.39	1030.58	926.78
72.5	1087.98	1955.23	1776.28	1760.64	858.10	866.03	787.66
75.0	884.32	1613.51	1436.12	1390.88	694.56	714.90	644.32
77.5	713.52	1288.17	1096.22	827.38	542.28	567.57	494.43
80.0	556.70	620.45	787.15	404.45	407.53	408.00	339.68

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : IHB4-LED-18L-LL-50.IES**

**CANDELA TABULATION - (Cont.)**

82.5	419.75	331.77	493.16	254.02	272.94	234.61	151.99
85.0	282.61	203.08	244.51	146.75	128.19	103.57	73.51
87.5	140.79	115.45	67.78	62.67	47.37	27.77	3.76
90.0	60.52	41.34	6.86	22.12	14.47	7.81	0.48
92.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
95.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00
97.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00
102.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
105.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00
107.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
110.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00
112.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
115.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00
117.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
120.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00
122.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
125.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00
127.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
130.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00
132.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
135.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00
137.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
140.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00
142.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
145.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00
147.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00
152.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
155.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00
157.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
160.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00
162.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
165.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00
167.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
170.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00
172.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
175.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00
177.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
180.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : IHB4-LED-18L-LL-50.IES**

**ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	2736.37	N.A.	12.80
0-30	5864.5	N.A.	27.40
0-40	9707.61	N.A.	45.40
0-60	17503.61	N.A.	81.80
0-80	21143.83	N.A.	98.80
0-90	21398.05	N.A.	100.00
10-90	20696.22	N.A.	96.70
20-40	6971.23	N.A.	32.60
20-50	11039.92	N.A.	51.60
40-70	10311.44	N.A.	48.20
60-80	3640.22	N.A.	17.00
70-80	1124.78	N.A.	5.30
80-90	254.22	N.A.	1.20
90-110	4.64	N.A.	0.00
90-120	4.64	N.A.	0.00
90-130	4.64	N.A.	0.00
90-150	4.64	N.A.	0.00
90-180	4.64	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	21402.69	N.A.	100.00

Total Luminaire Efficiency = N.A. %

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	701.83
10-20	2034.55
20-30	3128.12
30-40	3843.11
40-50	4068.68
50-60	3727.32
60-70	2515.44
70-80	1124.78
80-90	254.22
90-100	4.64
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : IHB4-LED-18L-LL-50.IES**

**COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD**

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	109	105	101	97	107	102	99	95	98	95	92	94	92	89	91	89	87	85
2	100	92	85	79	97	90	84	78	86	81	77	83	79	75	80	76	73	71
3	91	80	72	66	88	79	71	65	76	70	64	73	68	63	71	66	62	60
4	83	71	63	56	81	70	62	56	67	60	55	65	59	54	63	58	53	51
5	76	64	55	48	74	62	54	48	60	53	47	58	52	47	56	51	46	44
6	70	57	48	42	69	56	48	42	54	47	41	53	46	41	51	45	41	39
7	65	52	43	37	64	51	43	37	49	42	36	48	41	36	47	41	36	34
8	61	47	39	33	59	46	38	33	45	38	33	44	37	32	43	37	32	30
9	57	43	35	29	55	43	35	29	41	34	29	40	34	29	39	33	29	27
10	53	40	32	27	52	39	32	27	38	31	26	37	31	26	36	31	26	24

POLAR GRAPH



Maximum Candela = 7403.66 Located At Horizontal Angle = 157.5, Vertical Angle = 2.5  
# 1 - Vertical Plane Through Horizontal Angles (157.5 - 337.5) (Through Max. Cd.)  
# 2 - Horizontal Cone Through Vertical Angle (2.5) (Through Max. Cd.)