



**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : LPEC24-SM-LED-VHO-NW.IES**

**DESCRIPTION INFORMATION (From Photometric File)**

IESNA:LM-63-2002  
[TEST]LED-5819A  
[TESTLAB]LSI INDUSTRIES, INC  
[ISSUE DATE]02/26/16  
[TEST DATE]07/15/14  
[MANUFACT]LSI INDUSTRIES, INC  
[ABSOLUTE]NOTE: DATA SHOWN IS ABSOLUTE FOR THE SAMPLE PROVIDED.  
[OTHER]SCALED FROM ORIGINAL TEST DATA  
[OTHER]TEST PROCEDURE: IESNA LM-79-08  
[\_SEARCH\_SOURCE TYPE] LED  
[\_SEARCH\_APPLICATION] Indoor  
[LUMCAT]LPEC24-SM-LED-VHO-NW

**CHARACTERISTICS**

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	6190
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	104
Total Luminaire Watts	59.3
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.26
Spacing Criterion (90-270)	1.38
Spacing Criterion (Diagonal)	1.46
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	4.00 ft
Luminous Width (90-270)	2.00 ft
Luminous Height	0.00 ft

**LUMINANCE DATA (cd/sq.m)**

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	2277	2624	2888
55	2100	2665	3136
65	1917	2732	3479
75	1664	2921	4098
85	1477	3447	4496

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : LPEC24-SM-LED-VHO-NW.IES**

**CANDELA TABULATION**

	<u>0.0</u>	<u>22.5</u>	<u>45.0</u>	<u>67.5</u>	<u>90.0</u>
<b>0.0</b>	1867.39	1867.39	1867.39	1867.39	1867.39
<b>2.5</b>	1914.77	1889.02	1866.36	1844.73	1831.34
<b>5.0</b>	1910.65	1884.90	1863.27	1843.70	1830.31
<b>7.5</b>	1900.35	1875.63	1857.09	1840.61	1828.25
<b>10.0</b>	1885.93	1863.27	1847.82	1835.46	1825.16
<b>12.5</b>	1866.36	1845.76	1835.46	1827.22	1820.01
<b>15.0</b>	1840.61	1825.16	1820.01	1816.92	1811.77
<b>17.5</b>	1809.71	1798.38	1801.47	1805.59	1801.47
<b>20.0</b>	1773.66	1767.48	1779.84	1791.17	1790.14
<b>22.5</b>	1733.49	1732.46	1755.12	1774.69	1776.75
<b>25.0</b>	1689.20	1693.32	1726.28	1755.12	1760.27
<b>27.5</b>	1639.76	1650.06	1694.35	1733.49	1741.73
<b>30.0</b>	1586.20	1602.68	1658.30	1707.74	1720.10
<b>32.5</b>	1529.55	1553.24	1620.19	1679.93	1693.32
<b>35.0</b>	1468.78	1498.65	1578.99	1649.03	1664.48
<b>37.5</b>	1404.92	1442.00	1533.67	1614.01	1631.52
<b>40.0</b>	1337.97	1381.23	1485.26	1575.90	1596.50
<b>42.5</b>	1268.96	1315.31	1433.76	1535.73	1559.42
<b>45.0</b>	1197.89	1249.39	1380.20	1492.47	1519.25
<b>47.5</b>	1118.58	1179.35	1323.55	1447.15	1478.05
<b>50.0</b>	1044.42	1108.28	1263.81	1398.74	1433.76
<b>52.5</b>	970.26	1037.21	1203.04	1348.27	1387.41
<b>55.0</b>	896.10	965.11	1137.12	1290.59	1337.97
<b>57.5</b>	821.94	891.98	1071.20	1231.88	1281.32
<b>60.0</b>	747.78	817.82	1001.16	1171.11	1220.55
<b>62.5</b>	674.65	742.63	931.12	1106.22	1159.78
<b>65.0</b>	602.55	666.41	859.02	1040.30	1093.86
<b>67.5</b>	527.36	591.22	785.89	971.29	1025.88
<b>70.0</b>	454.23	519.12	711.73	900.22	953.78
<b>72.5</b>	386.25	447.02	636.54	822.97	877.56
<b>75.0</b>	320.33	378.01	562.38	739.54	788.98
<b>77.5</b>	257.50	313.12	484.10	648.90	692.16
<b>80.0</b>	199.82	249.26	401.70	548.99	588.13
<b>82.5</b>	145.23	188.49	315.18	435.69	460.41
<b>85.0</b>	95.79	128.75	223.51	291.49	291.49
<b>87.5</b>	46.35	69.01	106.09	110.21	97.85
<b>90.0</b>	0.00	0.00	0.00	0.00	0.00

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : LPEC24-SM-LED-VHO-NW.IES**

**ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	692.34	N.A.	11.20
0-30	1487.84	N.A.	24.00
0-40	2472.39	N.A.	39.90
0-60	4537.43	N.A.	73.30
0-80	5969.71	N.A.	96.40
0-90	6189.7	N.A.	100.00
10-90	6012.11	N.A.	97.10
20-40	1780.05	N.A.	28.80
20-50	2837.11	N.A.	45.80
40-70	2909.49	N.A.	47.00
60-80	1432.28	N.A.	23.10
70-80	587.83	N.A.	9.50
80-90	219.99	N.A.	3.60
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	6189.7	N.A.	100.00

Total Luminaire Efficiency = N.A. %

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	177.58
10-20	514.76
20-30	795.50
30-40	984.55
40-50	1057.05
50-60	1007.98
60-70	844.45
70-80	587.83
80-90	219.99
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : LPEC24-SM-LED-VHO-NW.IES**

**COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD**

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	107	102	97	93	105	100	95	91	95	92	89	91	89	86	88	85	83	81
2	97	88	80	74	94	86	79	73	82	77	72	79	74	70	76	72	68	66
3	88	77	68	61	85	75	67	60	72	65	59	69	63	58	66	61	57	55
4	80	67	58	51	78	66	57	51	63	56	50	61	54	49	59	53	48	46
5	74	60	51	44	71	59	50	43	57	49	43	55	48	42	53	47	42	40
6	68	54	44	38	66	53	44	38	51	43	37	49	42	37	48	41	36	34
7	63	49	40	33	61	48	39	33	46	38	33	45	38	32	43	37	32	30
8	58	44	35	29	57	44	35	29	42	35	29	41	34	29	40	33	29	27
9	54	41	32	26	53	40	32	26	39	31	26	38	31	26	37	30	26	24
10	51	37	29	24	50	37	29	24	36	29	24	35	28	24	34	28	23	22

POLAR GRAPH



Maximum Candela = 1914.77 Located At Horizontal Angle = 0, Vertical Angle = 2.5

# 1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)

# 2 - Horizontal Cone Through Vertical Angle (2.5) (Through Max. Cd.)