



IES ROAD REPORT
PHOTOMETRIC FILENAME : MCOWP-27-45.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] 2862
[TESTLAB] TUV SUD America
[TESTDATE] 1/19/2016 3:41:27 PM
[MANUFAC]LSI INDUSTRIES, INC
[ISSUEDATE] 5/1/2017
[OTHER]TEST PROCEDURE: IESNA LM-79-08
[_ABSOLUTE]NOTE: DATA SHOWN IS ABSOLUTE FOR THE SAMPLE PROVIDED
[_SEARCH_SOURCETYPE] LED
[_SEARCH_APPLICATION] Outdoor
[LUMCAT] MCOWP-27-45

CHARACTERISTICS

IES Classification	Type VS
Longitudinal Classification	Very Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	3238
Downward Total Efficiency	N.A. (absolute)
Total Luminaire Efficiency	N.A. (absolute)
Luminaire Efficacy Rating (LER)	121
Total Luminaire Watts	26.85
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	1219.36
Maximum Candela Angle	135H 2.5V
Maximum Candela (<90 Degrees Vertical)	1219.36
Maximum Candela Angle (<90 Degrees Vertical)	135H 2.5V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Luminaire Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	40.87 (1.3% Luminaire Lumens)
Cutoff Classification (deprecated)	N.A. (absolute)

IES ROAD REPORT
PHOTOMETRIC FILENAME : MCOWP-27-45.IES

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	476.9	N.A.	14.7
FM - Front-Medium (30-60)	892.2	N.A.	27.6
FH - Front-High (60-80)	230.7	N.A.	7.1
FVH - Front-Very High (80-90)	1.7	N.A.	0.1
BL - Back-Low (0-30)	482.1	N.A.	14.9
BM - Back-Medium (30-60)	904.0	N.A.	27.9
BH - Back-High (60-80)	247.5	N.A.	7.6
BVH - Back-Very High (80-90)	2.4	N.A.	0.1
UL - Uplight-Low (90-100)	0.0	N.A.	0.0
UH - Uplight-High (100-180)	0.0	N.A.	0.0
Total	3237.5	N.A.	100.0
BUG Rating	B1-U0-G0		

IES ROAD REPORT
PHOTOMETRIC FILENAME : MCOWP-27-45.IES

CANDELA TABULATION

Vert. Angles	Horizontal Angles									
	<u>0.0</u>	<u>22.5</u>	<u>45.0</u>	<u>67.5</u>	<u>90.0</u>	<u>112.5</u>	<u>135.0</u>	<u>157.5</u>	<u>180.0</u>	<u>202.5</u>
0.0	1216.59	1216.59	1216.59	1216.59	1216.59	1216.59	1216.59	1216.59	1216.59	1216.59
2.5	1216.47	1218.24	1218.89	1218.30	1219.35	1219.21	1219.36	1218.36	1218.50	1218.21
5.0	1213.02	1215.56	1214.36	1218.81	1218.86	1216.80	1216.98	1218.21	1215.13	1214.18
7.5	1206.75	1208.64	1211.60	1215.09	1217.41	1213.37	1212.94	1213.71	1211.60	1208.65
10.0	1196.97	1199.84	1205.29	1208.84	1213.20	1208.15	1207.69	1207.65	1206.90	1201.92
12.5	1182.67	1188.01	1195.24	1200.28	1205.13	1201.41	1200.52	1200.00	1199.69	1193.01
15.0	1165.59	1174.13	1182.42	1189.50	1194.49	1193.42	1190.88	1190.00	1190.01	1181.36
17.5	1148.96	1158.57	1167.63	1176.69	1179.88	1182.93	1178.58	1176.71	1177.54	1167.73
20.0	1131.84	1141.30	1151.40	1160.78	1161.83	1167.75	1163.71	1160.93	1164.40	1152.25
22.5	1111.33	1122.24	1133.71	1142.25	1143.36	1149.40	1146.61	1142.85	1146.62	1133.86
25.0	1088.53	1100.42	1113.49	1122.19	1125.10	1128.74	1126.73	1122.55	1127.17	1112.77
27.5	1065.92	1077.70	1091.33	1099.80	1106.70	1106.56	1104.99	1100.10	1105.61	1089.75
30.0	1038.44	1051.39	1066.45	1075.16	1083.16	1082.81	1080.51	1075.44	1080.42	1064.99
32.5	1008.21	1021.76	1038.15	1048.70	1054.63	1057.21	1053.88	1047.17	1053.12	1037.36
35.0	975.80	990.85	1007.25	1018.69	1026.19	1028.58	1025.03	1017.00	1022.26	1006.35
37.5	943.35	957.46	973.71	986.43	996.67	997.33	993.36	982.72	986.56	971.92
40.0	892.69	909.52	937.29	952.94	963.09	963.55	959.21	940.58	944.41	928.49
42.5	847.40	866.29	892.83	912.31	921.13	922.24	917.03	881.57	881.61	871.72
45.0	806.03	826.08	845.39	859.95	865.20	871.04	867.25	823.97	825.66	814.74
47.5	763.18	783.14	803.23	815.42	820.49	826.97	816.72	766.73	768.71	759.02
50.0	695.04	729.75	757.88	766.14	768.64	777.25	762.50	704.98	705.94	701.46
52.5	625.93	664.14	707.33	711.28	708.20	721.41	704.09	641.22	641.83	640.64
55.0	557.10	593.12	651.90	649.47	643.36	659.13	640.90	579.52	579.01	578.32
57.5	486.86	520.92	586.89	585.03	581.81	595.59	572.50	524.81	530.48	521.86
60.0	429.49	453.78	509.57	523.59	526.74	535.68	499.49	475.55	484.70	471.33
62.5	375.11	396.41	428.11	466.52	474.45	477.05	426.87	425.41	438.34	421.60
65.0	320.88	341.30	350.83	409.67	415.02	416.66	361.12	372.61	385.68	368.95
67.5	228.32	270.16	285.73	350.67	354.64	352.41	305.21	290.55	295.12	299.66
70.0	164.35	195.19	231.66	287.22	292.88	285.15	252.77	220.87	230.76	216.30
72.5	101.07	125.47	170.93	215.63	219.14	215.24	190.79	148.84	152.55	159.66
75.0	42.42	66.48	104.81	142.05	151.07	145.37	123.82	85.58	95.37	94.82
77.5	10.68	23.78	53.11	78.41	86.08	88.83	70.47	35.27	45.88	47.51
80.0	1.44	4.59	18.24	34.39	35.68	40.87	28.72	9.32	10.67	16.99
82.5	0.02	0.35	2.19	6.20	5.83	9.78	5.23	1.32	1.45	2.80
85.0	0.00	0.00	0.00	0.00	0.00	0.04	0.04	0.00	0.00	0.02
87.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00


Vert. Angles	Horizontal Angles						
	<u>225.0</u>	<u>247.5</u>	<u>270.0</u>	<u>292.5</u>	<u>315.0</u>	<u>337.5</u>	<u>360.0</u>
0.0	1216.59	1216.59	1216.59	1216.59	1216.59	1216.59	1216.59
2.5	1217.81	1215.37	1212.51	1214.47	1216.04	1215.73	1216.47
5.0	1213.27	1211.30	1207.80	1210.24	1210.57	1210.60	1213.02
7.5	1206.89	1205.02	1200.45	1203.89	1203.07	1203.94	1206.75
10.0	1198.58	1195.77	1191.27	1194.29	1193.17	1194.88	1196.97
12.5	1188.14	1184.77	1181.02	1181.68	1180.78	1183.10	1182.67
15.0	1175.08	1170.36	1167.14	1166.44	1165.82	1168.57	1165.59
17.5	1160.48	1154.39	1150.51	1149.13	1148.90	1152.09	1148.96
20.0	1144.01	1136.20	1131.67	1128.92	1130.28	1134.24	1131.84
22.5	1124.92	1116.26	1110.04	1108.74	1109.60	1114.51	1111.33
25.0	1103.45	1092.93	1086.66	1083.68	1086.67	1091.93	1088.53
27.5	1079.25	1067.25	1061.07	1057.50	1061.50	1066.66	1065.92

IES ROAD REPORT
PHOTOMETRIC FILENAME : MCOWP-27-45.IES

CANDELA TABULATION - (Cont.)

30.0	1052.94	1040.02	1032.79	1029.11	1034.22	1039.49	1038.44
32.5	1023.87	1010.59	1000.77	998.01	1003.92	1010.54	1008.21
35.0	992.42	978.98	965.16	965.84	971.59	979.39	975.80
37.5	959.05	942.43	925.92	929.04	937.15	945.95	943.35
40.0	916.46	890.68	868.78	875.36	890.53	904.65	892.69
42.5	868.82	839.15	816.46	823.95	844.59	855.85	847.40
45.0	822.77	788.80	765.42	774.43	802.32	815.27	806.03
47.5	771.75	736.90	713.47	721.45	754.89	771.68	763.18
50.0	713.21	685.40	665.67	669.25	702.24	722.56	695.04
52.5	651.18	634.65	616.90	619.20	646.65	663.59	625.93
55.0	585.06	584.90	567.87	569.33	588.37	594.87	557.10
57.5	516.93	534.36	518.11	519.05	527.83	524.52	486.86
60.0	451.27	483.20	469.50	467.16	462.88	454.95	429.49
62.5	390.56	428.17	417.30	415.00	394.66	392.70	375.11
65.0	336.43	368.99	360.07	361.71	328.18	336.32	320.88
67.5	286.59	306.36	305.14	306.96	268.47	271.84	228.32
70.0	237.98	245.02	239.11	245.07	216.72	197.57	164.35
72.5	178.50	178.19	180.53	180.79	161.48	137.67	101.07
75.0	117.98	123.17	121.44	118.91	103.79	79.20	42.42
77.5	68.21	74.84	68.34	65.69	55.78	33.54	10.68
80.0	28.77	35.15	27.43	27.74	21.11	8.98	1.44
82.5	6.50	8.86	5.23	6.24	3.70	0.98	0.02
85.0	0.39	0.77	0.32	0.45	0.00	0.00	0.00
87.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00
90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00


COEFFICIENTS OF UTILIZATION



FLUX DISTRIBUTION


	Lumens	Percent Of Luminaire
Downward Street Side	1601.5	49.5
Downward House Side	1636.0	50.5
Downward Total	3237.5	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	3237.5	100.0

POLAR GRAPH




Maximum Candela = 1219.36 Located At Horizontal Angle = 135, Vertical Angle = 2.5
1 - Vertical Plane Through Horizontal Angles (135 - 315) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (2.5) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
Front: Low=476.9, Medium=892.2, High=230.7, Very High=1.7
Back: Low=482.1, Medium=904.0, High=247.5, Very High=2.4
Uplight: Low=0.0, High=0.0

BUG Rating : B1-U0-G0