



IES ROAD REPORT

PHOTOMETRIC FILENAME : TLWP-LED-07L-50.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] 3760

[TESTLAB] TUV SUD America

[ISSUE DATE] 2/20/2020

[TEST DATE] 8/29/2019 10:22:24 AM

[MANUFAC] LSI INDUSTRIES, INC

[LUMCAT] TLWP-LED-07L-50

[OTHER] TEST PROCEDURE: IESNA

[ABSOLUTE] NOTE: DATA SHOWN IS ABSOLUTE FOR THE SAMPLE PROVIDED

[SEARCH_SOURCETYPE] LED

[SEARCH_APPLICATION] Outdoor

CHARACTERISTICS

IES Classification	Type IV
Longitudinal Classification	Very Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	7276
Downward Total Efficiency	N.A. (absolute)
Total Luminaire Efficiency	N.A. (absolute)
Luminaire Efficacy Rating (LER)	119
Total Luminaire Watts	61
Ballast Factor	1.00
Upward Waste Light Ratio	0.22
Maximum Candela	2316.53
Maximum Candela Angle	360H 55V
Maximum Candela (<90 Degrees Vertical)	2316.53
Maximum Candela Angle (<90 Degrees Vertical)	360H 55V
Maximum Candela At 90 Degrees Vertical	1772.45 (24.4% Luminaire Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	2017.27 (27.7% Luminaire Lumens)
Cutoff Classification (deprecated)	N.A. (absolute)

IES ROAD REPORT
PHOTOMETRIC FILENAME : TLWP-LED-07L-50.IES

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	652.8	N.A.	9.0
FM - Front-Medium (30-60)	1909.7	N.A.	26.2
FH - Front-High (60-80)	1484.3	N.A.	20.4
FVH - Front-Very High (80-90)	643.1	N.A.	8.8
BL - Back-Low (0-30)	359.0	N.A.	4.9
BM - Back-Medium (30-60)	472.3	N.A.	6.5
BH - Back-High (60-80)	128.9	N.A.	1.8
BVH - Back-Very High (80-90)	26.7	N.A.	0.4
UL - Uplight-Low (90-100)	544.5	N.A.	7.5
UH - Uplight-High (100-180)	1054.2	N.A.	14.5
Total	7275.5	N.A.	100.0
BUG Rating	B1-U5-G4		

IES ROAD REPORT
PHOTOMETRIC FILENAME : TLWP-LED-07L-50.IES

CANDELA TABULATION

Vert. Angles	Horizontal Angles									
	0.0	22.5	45.0	67.5	90.0	112.5	135.0	157.5	180.0	202.5
0.0	1262.86	1262.86	1262.86	1262.86	1262.86	1262.86	1262.86	1262.86	1262.86	1262.86
2.5	1364.36	1333.83	1313.03	1287.21	1256.47	1224.82	1198.32	1181.78	1198.91	1181.78
5.0	1443.19	1405.60	1365.61	1313.18	1251.44	1187.89	1137.48	1105.09	1113.34	1105.09
7.5	1515.50	1472.20	1415.09	1336.09	1242.93	1150.05	1077.90	1035.35	1035.84	1035.35
10.0	1581.99	1535.15	1461.77	1355.61	1232.21	1111.33	1019.85	969.42	963.95	969.42
12.5	1647.30	1590.93	1502.95	1371.24	1217.69	1071.28	967.53	908.31	901.02	908.31
15.0	1715.55	1644.12	1538.61	1383.00	1199.59	1029.22	915.80	844.40	833.46	844.40
17.5	1785.68	1703.03	1569.16	1389.77	1178.81	987.92	861.91	782.52	767.92	782.52
20.0	1849.38	1759.07	1597.78	1392.98	1155.84	947.23	808.27	720.82	700.46	720.82
22.5	1909.77	1813.82	1630.86	1392.69	1130.31	905.48	755.94	659.31	632.26	659.31
25.0	1963.63	1862.19	1660.61	1389.46	1102.60	861.89	703.99	596.05	563.83	596.05
27.5	2009.55	1904.66	1686.66	1383.06	1073.69	817.25	652.51	533.85	503.44	533.85
30.0	2044.70	1939.29	1708.67	1375.58	1042.21	775.23	601.51	478.91	451.18	478.91
32.5	2085.36	1966.98	1725.34	1368.74	1014.19	732.88	550.24	430.36	406.35	430.36
35.0	2125.57	1997.45	1738.71	1360.50	982.09	689.95	502.37	390.38	369.87	390.38
37.5	2147.93	2027.36	1747.53	1350.09	949.29	648.59	458.01	354.75	334.83	354.75
40.0	2176.07	2043.37	1753.91	1339.94	916.40	608.17	415.04	325.35	308.54	325.35
42.5	2224.96	2061.88	1758.65	1329.19	881.99	567.86	375.33	296.88	282.72	296.88
45.0	2253.36	2091.75	1759.46	1316.09	848.73	528.29	339.91	270.14	254.88	270.14
47.5	2259.16	2112.27	1759.31	1301.21	813.01	488.68	307.97	244.65	231.11	244.65
50.0	2275.66	2113.06	1759.05	1283.66	774.93	450.58	278.05	216.30	205.04	216.30
52.5	2307.84	2118.59	1756.01	1263.72	735.69	413.27	249.93	188.94	177.65	188.94
55.0	2316.53	2131.76	1745.84	1241.78	695.68	377.13	223.29	160.92	149.98	160.92
57.5	2288.16	2123.54	1728.54	1216.30	654.38	341.15	195.51	132.26	118.97	132.26
60.0	2252.33	2090.04	1706.92	1189.50	612.13	306.77	168.10	101.89	85.79	101.89
62.5	2220.59	2049.71	1675.85	1157.54	570.13	273.32	140.72	70.63	55.86	70.63
65.0	2194.63	2011.48	1633.20	1121.92	525.83	241.45	113.01	40.06	25.41	40.06
67.5	2170.14	1978.18	1585.69	1085.71	478.82	210.21	85.71	16.75	0.00	16.75
70.0	2149.01	1947.62	1536.84	1040.59	431.95	180.46	60.77	2.85	0.00	2.85
72.5	2125.43	1919.45	1490.56	990.99	384.92	153.00	45.27	1.86	0.00	1.86
75.0	2099.75	1889.01	1445.50	938.43	340.71	128.16	33.53	1.39	0.00	1.39
77.5	2063.01	1852.31	1399.99	885.03	297.07	107.81	29.47	0.98	0.00	0.98
80.0	2017.27	1809.14	1351.92	831.20	255.71	93.15	26.81	0.64	0.00	0.64
82.5	1963.64	1757.23	1300.62	778.01	218.17	82.16	24.74	0.41	0.01	0.41
85.0	1903.55	1701.82	1246.65	723.76	186.34	75.32	22.79	0.32	0.00	0.32
87.5	1842.02	1642.53	1192.41	670.75	162.31	70.66	21.12	0.16	0.00	0.16
90.0	1772.45	1579.16	1136.55	621.84	144.23	67.13	19.43	0.09	0.07	0.09
92.5	1695.60	1509.47	1079.20	575.70	132.31	63.50	18.08	0.22	0.03	0.22
95.0	1612.89	1434.88	1020.99	533.06	123.88	60.36	16.63	0.16	0.14	0.16
97.5	1524.42	1354.58	959.56	491.39	116.43	56.87	15.07	0.07	0.42	0.07
100.0	1434.41	1274.51	898.17	452.66	109.50	53.49	13.77	0.10	0.11	0.10
102.5	1344.72	1194.97	842.13	416.17	102.56	50.25	12.74	0.00	0.03	0.00
105.0	1257.12	1115.98	784.67	383.69	96.18	47.14	11.50	0.05	0.02	0.05
107.5	1165.67	1038.80	728.11	353.54	89.46	44.26	9.94	0.02	0.07	0.02
110.0	1077.20	967.43	673.40	326.16	83.04	41.22	8.82	0.00	0.00	0.00
112.5	991.22	892.63	621.50	300.79	76.58	38.37	7.56	0.03	0.09	0.03
115.0	914.29	817.35	570.34	276.79	70.24	35.63	6.67	0.03	0.00	0.03
117.5	833.92	746.89	522.61	254.56	64.52	32.75	5.69	0.11	0.52	0.11
120.0	760.80	682.46	477.80	232.77	59.43	29.97	4.90	0.19	0.80	0.19
122.5	691.91	622.43	437.36	213.53	53.84	27.08	4.16	0.35	0.73	0.35
125.0	628.15	567.70	401.27	195.15	48.01	24.24	3.50	0.51	0.90	0.51
127.5	567.66	514.97	367.34	177.11	42.25	21.52	3.16	0.92	1.23	0.92
130.0	513.26	467.55	335.77	159.90	35.69	18.86	2.74	1.13	1.61	1.13

IES ROAD REPORT
PHOTOMETRIC FILENAME : TLWP-LED-07L-50.IES

CANDELA TABULATION - (Cont.)

132.5	464.19	424.08	306.43	144.27	29.78	16.53	2.69	1.56	1.99	1.56
135.0	420.78	385.50	278.99	131.46	24.32	13.95	2.56	1.83	2.15	1.83
137.5	381.78	350.61	254.63	119.70	19.91	11.55	2.11	1.92	2.28	1.92
140.0	344.18	317.43	234.01	107.67	16.32	9.45	2.03	2.19	2.35	2.19
142.5	309.23	290.71	219.16	93.85	13.25	7.58	2.04	2.49	2.86	2.49
145.0	289.15	269.09	203.01	73.76	11.27	6.02	2.13	2.79	2.93	2.79
147.5	268.37	251.71	190.86	63.02	9.32	4.26	2.49	3.05	3.31	3.05
150.0	259.59	240.09	174.59	54.10	7.57	3.24	2.69	3.13	3.28	3.13
152.5	242.24	221.76	154.57	42.21	5.90	2.56	2.64	3.03	3.24	3.03
155.0	213.17	196.05	130.74	24.18	4.62	2.52	2.90	3.31	3.16	3.31
157.5	180.36	164.81	103.06	8.49	3.92	2.51	2.84	3.35	3.27	3.35
160.0	145.99	131.95	67.49	4.37	3.09	2.70	2.86	3.48	3.27	3.48
162.5	110.93	99.26	33.41	2.56	2.69	2.82	2.93	3.11	3.12	3.11
165.0	68.14	57.19	10.48	2.32	2.49	2.81	2.90	3.34	3.23	3.34
167.5	17.34	16.10	2.23	2.32	2.69	2.87	3.08	3.09	3.38	3.09
170.0	2.03	2.13	2.35	2.62	2.74	2.95	3.26	3.31	3.39	3.31
172.5	2.14	2.39	2.66	2.58	2.83	3.07	3.22	3.08	3.32	3.08
175.0	2.57	2.58	2.80	2.88	2.89	3.13	3.09	3.15	3.09	3.15
177.5	2.90	2.70	2.85	3.15	3.19	3.13	2.99	3.01	3.08	3.01
180.0	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00

Vert. Angles **Horizontal Angles**


	<u>225.0</u>	<u>247.5</u>	<u>270.0</u>	<u>292.5</u>	<u>315.0</u>	<u>337.5</u>	<u>360.0</u>
0.0	1262.86	1262.86	1262.86	1262.86	1262.86	1262.86	1262.86
2.5	1198.32	1224.82	1256.47	1287.21	1313.03	1333.83	1364.36
5.0	1137.48	1187.89	1251.44	1313.18	1365.61	1405.60	1443.19
7.5	1077.90	1150.05	1242.93	1336.09	1415.09	1472.20	1515.50
10.0	1019.85	1111.33	1232.21	1355.61	1461.77	1535.15	1581.99
12.5	967.53	1071.28	1217.69	1371.24	1502.95	1590.93	1647.30
15.0	915.80	1029.22	1199.59	1383.00	1538.61	1644.12	1715.55
17.5	861.91	987.92	1178.81	1389.77	1569.16	1703.03	1785.68
20.0	808.27	947.23	1155.84	1392.98	1597.78	1759.07	1849.38
22.5	755.94	905.48	1130.31	1392.69	1630.86	1813.82	1909.77
25.0	703.99	861.89	1102.60	1389.46	1660.61	1862.19	1963.63
27.5	652.51	817.25	1073.69	1383.06	1686.66	1904.66	2009.55
30.0	601.51	775.23	1042.21	1375.58	1708.67	1939.29	2044.70
32.5	550.24	732.88	1014.19	1368.74	1725.34	1966.98	2085.36
35.0	502.37	689.95	982.09	1360.50	1738.71	1997.45	2125.57
37.5	458.01	648.59	949.29	1350.09	1747.53	2027.36	2147.93
40.0	415.04	608.17	916.40	1339.94	1753.91	2043.37	2176.07
42.5	375.33	567.86	881.99	1329.19	1758.65	2061.88	2224.96
45.0	339.91	528.29	848.73	1316.09	1759.46	2091.75	2253.36
47.5	307.97	488.68	813.01	1301.21	1759.31	2112.27	2259.16
50.0	278.05	450.58	774.93	1283.66	1759.05	2113.06	2275.66
52.5	249.93	413.27	735.69	1263.72	1756.01	2118.59	2307.84
55.0	223.29	377.13	695.68	1241.78	1745.84	2131.76	2316.53
57.5	195.51	341.15	654.38	1216.30	1728.54	2123.54	2288.16
60.0	168.10	306.77	612.13	1189.50	1706.92	2090.04	2252.33
62.5	140.72	273.32	570.13	1157.54	1675.85	2049.71	2220.59
65.0	113.01	241.45	525.83	1121.92	1633.20	2011.48	2194.63
67.5	85.71	210.21	478.82	1085.71	1585.69	1978.18	2170.14
70.0	60.77	180.46	431.95	1040.59	1536.84	1947.62	2149.01
72.5	45.27	153.00	384.92	990.99	1490.56	1919.45	2125.43
75.0	33.53	128.16	340.71	938.43	1445.50	1889.01	2099.75
77.5	29.47	107.81	297.07	885.03	1399.99	1852.31	2063.01

IES ROAD REPORT
PHOTOMETRIC FILENAME : TLWP-LED-07L-50.IES

CANDELA TABULATION - (Cont.)

80.0	26.81	93.15	255.71	831.20	1351.92	1809.14	2017.27
82.5	24.74	82.16	218.17	778.01	1300.62	1757.23	1963.64
85.0	22.79	75.32	186.34	723.76	1246.65	1701.82	1903.55
87.5	21.12	70.66	162.31	670.75	1192.41	1642.53	1842.02
90.0	19.43	67.13	144.23	621.84	1136.55	1579.16	1772.45
92.5	18.08	63.50	132.31	575.70	1079.20	1509.47	1695.60
95.0	16.63	60.36	123.88	533.06	1020.99	1434.88	1612.89
97.5	15.07	56.87	116.43	491.39	959.56	1354.58	1524.42
100.0	13.77	53.49	109.50	452.66	898.17	1274.51	1434.41
102.5	12.74	50.25	102.56	416.17	842.13	1194.97	1344.72
105.0	11.50	47.14	96.18	383.69	784.67	1115.98	1257.12
107.5	9.94	44.26	89.46	353.54	728.11	1038.80	1165.67
110.0	8.82	41.22	83.04	326.16	673.40	967.43	1077.20
112.5	7.56	38.37	76.58	300.79	621.50	892.63	991.22
115.0	6.67	35.63	70.24	276.79	570.34	817.35	914.29
117.5	5.69	32.75	64.52	254.56	522.61	746.89	833.92
120.0	4.90	29.97	59.43	232.77	477.80	682.46	760.80
122.5	4.16	27.08	53.84	213.53	437.36	622.43	691.91
125.0	3.50	24.24	48.01	195.15	401.27	567.70	628.15
127.5	3.16	21.52	42.25	177.11	367.34	514.97	567.66
130.0	2.74	18.86	35.69	159.90	335.77	467.55	513.26
132.5	2.69	16.53	29.78	144.27	306.43	424.08	464.19
135.0	2.56	13.95	24.32	131.46	278.99	385.50	420.78
137.5	2.11	11.55	19.91	119.70	254.63	350.61	381.78
140.0	2.03	9.45	16.32	107.67	234.01	317.43	344.18
142.5	2.04	7.58	13.25	93.85	219.16	290.71	309.23
145.0	2.13	6.02	11.27	73.76	203.01	269.09	289.15
147.5	2.49	4.26	9.32	63.02	190.86	251.71	268.37
150.0	2.69	3.24	7.57	54.10	174.59	240.09	259.59
152.5	2.64	2.56	5.90	42.21	154.57	221.76	242.24
155.0	2.90	2.52	4.62	24.18	130.74	196.05	213.17
157.5	2.84	2.51	3.92	8.49	103.06	164.81	180.36
160.0	2.86	2.70	3.09	4.37	67.49	131.95	145.99
162.5	2.93	2.82	2.69	2.56	33.41	99.26	110.93
165.0	2.90	2.81	2.49	2.32	10.48	57.19	68.14
167.5	3.08	2.87	2.69	2.32	2.23	16.10	17.34
170.0	3.26	2.95	2.74	2.62	2.35	2.13	2.03
172.5	3.22	3.07	2.83	2.58	2.66	2.39	2.14
175.0	3.09	3.13	2.89	2.88	2.80	2.58	2.57
177.5	2.99	3.13	3.19	3.15	2.85	2.70	2.90
180.0	2.00	2.00	2.00	2.00	2.00	2.00	2.00


COEFFICIENTS OF UTILIZATION



FLUX DISTRIBUTION


	Lumens	Percent Of Luminaire
Downward Street Side	4689.9	64.5
Downward House Side	986.9	13.6
Downward Total	5676.8	78.0
Upward Street Side	1544.0	21.2
Upward House Side	54.7	0.8
Upward Total	1598.7	22.0
Total Flux	7275.5	100.0

POLAR GRAPH




Maximum Candela = 2316.53 Located At Horizontal Angle = 360, Vertical Angle = 55
1 - Vertical Plane Through Horizontal Angles (360 - 180) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (55) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
Front: Low=652.8, Medium=1909.7, High=1484.3, Very High=643.1
Back: Low=359.0, Medium=472.3, High=128.9, Very High=26.7
Uplight: Low=544.5, High=1054.2

BUG Rating : B1-U5-G4