

**(CSL)****LED Contemporary Surface Light**

wet location

**OVERVIEW**

Lumen Range (AC/DC)	1080 / 260
CCT	5000K
Wattage	11
Efficacy (LPW)	98

**QUICK LINKS**[Ordering Guide](#)[Dimensions](#)**FEATURES & SPECIFICATIONS****Construction**

- Die-cast aluminum housing
- UV-stabilized, vandal resistant, polycarbonate lens
- Available in Bronze, White, Black, and Satin Aluminum

**Optical System**

- 11 watts, 5000K CCT LED
- Dissipates 1080 lumens in AC mode and 260 lumens in DC mode
- Can be used as a Normally-ON or Normally-OFF luminaire as well as on a switched circuit.
- Minimum CRI of 70

**Electrical**

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing .
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.

- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- Self-diagnostic feature performs monthly and bi-annual tests to ensure reliable operation and meets electrical and life safety codes.
- Photocell control sensor included as standard for use as dusk-to-dawn luminaire.
- Field-selectable wiring allows for AC operation of unit to be controlled using a wall-switch, photocell or other switching mechanism.

**Battery**

- Maintenance-free NiCad Battery
- Standard Operating temperatures: 0°C to 40°C (32°F to 104°F)
- CT - Cold Temp Operation Option: -20°C to 50°C (-4°F to 122°F)

**Installation**

- Universal J-box mounting pattern on back plate for wall mount
- Can be surface mounted using the ½" conduit entry point at top of housing

**Warranty**

- 3 year warranty on all electronics and housing.
- 2 year pro-rated warranty on battery.

**Listings**

- UL 924
- cULus
- NFPA 101
- NEC





# LED Contemporary Surface Light

## ORDERING GUIDE

[Back to Quick Links](#)

TYPICAL ORDER EXAMPLE: **CSL ACEM DB CT**

Family	Battery	Housing Color	Controls
CSL - Contemporary Surface Light	ACEM - Normally on with Emergency Lighting	DB - Dark Bronze W - White BK - Black SA - Satin Aluminum	CT - Cold Temp Operation

## PRODUCT DIMENSIONS

