



Catalog #: _____ Project: _____

Prepared By: _____ Date: _____ Type: _____

AirLink™ BlueTechnology Partner **SILVAIR**

Wall Dimmer 4 Button Switch



The AirLink Blue wall dimmer 4 button switch provides multi-level wireless control based on manual activation of the switch. Multiple fixtures can be grouped to be controlled by a single switch. Controls 0-10 VDC LED drivers and is rated for indoor installations. The 4 button switch enables manual on/off, dim up/down control, scene recall or tunable white control. Switch utilizes a Bluetooth Low Energy (BLE) mesh network. Dim levels and schedules can be set through LSI AirLink Blue Android or iOS app.



FEATURES & SPECIFICATIONS

Construction

- Wall dimmer 4 button switch provides multi-level wireless control based on manual activation of the switches.

Electrical

- Wall dimmer switch utilizes Bluetooth Low Energy (BLE) mesh network.
- Multiple fixtures can be grouped to be controlled by a single switch. Controls 0-10 VDC LED drivers and is rated for indoor installations.
- The 4 button switch enables manual on/off, dim up/down control, scene recall or tunable white control.
- Dim levels and schedules can be set through LSI AirLink Blue iOS app.

- Max Bluetooth range is 50' - 65' (15m - 20 m) and highly dependent on the integration of fixtures, surrounding environment. It is recommended to conduct testing for range accuracy.
- 120-277 VAC, 60Hz

Installation

- Wall dimmer 4 button switch mounts into a standard single gang wall box.
- Cover plate is standard single Decora™ style (supplied by others).
- Operating temperature range of 0°C to + 55°C (32°F to 131°F).

Warranty

- 5-year limited warranty. Refer to <https://www.lsicorp.com/resources/terms-conditions-warranty/> for more information.

Listings

- FCC
- UL
- Bluetooth

ORDERING GUIDE

| Catalog Number Suffix | Description | Part Number |
|-----------------------|--|-------------|
| ALBWS MW4B WH | AirLink Blue wall dimmer 4 button switch white | 760921 |





PRODUCT DIMENSIONS

