



Catalog #: _____ Project: _____

Prepared By: _____ Date: _____ Type: _____

LSWL

Wet Location Emergency Unit



wet location



FEATURES & SPECIFICATIONS

Construction

- UL 94 5VA flame retardant, impact resistant, polycarbonate housing
- Fully gasketed and sealed hinged cover
- Standard finish: Gray and Black

Optical System

- Fully adjustable, high-intensity LED heads
- 1.9 Watts per lamp head

Electrical

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz
- Solid-state transfer detects loss of line voltage and automatically switches to emergency mode

- Test button to provide manual verification of the transfer circuit and emergency lamps
- Remote capable up to 3.7 Watts powers up to two SRL remote lamp heads

Battery

- Maintenance free NiCad Battery
- Operating Temperatures -20°C to 50°C (-4°F to 122°F)

Installation

- Universal J-box mounting pattern and gasket provided
- Suitable for surface wall mount applications

Warranty

- 5 year warranty on all electronics and housing
- Separate 5 year pro-rated warranty on the battery

Listings

- UL 924
- NFPA 101
- NEC
- Wet Location Rated
- UL Listed 90 minute emergency run time, 24 hour recharge time

ORDERING GUIDE

TYPICAL ORDER EXAMPLE: **LSWL GY**

Prefix	Housing Color	Options
LSWL - Wet Location Emergency Unit	GY - Gray BK - Black	VL - Vandal Guard (back mount)

PRODUCT DIMENSIONS

