



Traditional Wall Light (TMWP)

Medium



OVERVIEW

Lumen Package (lm)	4,000
Wattage Range (W)	31
Efficacy Range (LPW)	125 - 130
Weight lbs (kg)	6.6 (3.0)

QUICK LINKS

FEATURES & SPECIFICATIONS

Construction

- Rugged traditional aluminum die cast housing provides proven environmental protection for LED modules.
- Traditional fixture design provides a familiar look and standard installation requirements.
- Retaining this look allows the ability to upgrade fixtures gradually, while retaining the same overall fixture appearance throughout a facility.
- Patent pending thermal stacking technology system features a unique internal design that allows for lower operating temperatures which results in a brighter, whiter light, more stable color and longer LED and driver life.
- LEDs manufactured for the TMWP series utilize Epoxy Guard conformal coating which reduces the chance of board corrosion.

Optical System

- Borosilicate glass lens.
- Lens assembly is designed to provide high efficiency and to target the light where needed to satisfy outdoor lighting requirements.
- Positioning of the LEDs result in the light being directed to desired locations eliminating glare and offensive light.

- Available in 5000K, 4000K and 3000K color temperatures per ANSI C78.377.
- Minimum CRI of 80.

Electrical

- High-performance driver features overvoltage, under-voltage, short-circuit and over temperature protection.
- 0-10V dimming (10% - 100%) standard.
- Standard Universal Voltage (120-277 VAC) Input 50/60 Hz
- Total harmonic distortion: <20%
- Operating temperature: -40°C to +40°C (-40°F to +104°F).
- Power factor: >0.90
- Components are fully encased in potting material for moisture resistance. Driver complies with FCC standards. Driver and key electronic components can easily be accessed.
- Minimum 2.5kV surge rating.

Controls

- Optional factory installed electronic button photocontrol (apertures for field install).

Installation

- Fixture retains the same knock-out sizes and positions as previous models, reducing wiring costs.

Warranty

- LSI luminaires carry a 5-year limited warranty. Refer to <https://www.lsicorp.com/resources/terms-conditions-warranty/> for more information.
- 1 Year warranty on optional button photocell.
- 1 Year warranty on optional Battery Back Up. Test regularly in accordance with local codes.

Listings

- Listed to UL 1598 and UL 8750.
- CSA Listed.
- Meets Buy American Act requirements.
- RoHS Compliant.
- Suitable for wet locations

Traditional Wall Light (TMWP) Medium

Type : _____

 **Have questions?** Call us at (800) 436-7800

ORDERING GUIDE

TYPICAL ORDER EXAMPLE: TMWP 4L UNV 40 BZA PCI120						
Prefix	Lumen Package	Voltage	Dimming	Color Temperature	Finish	Controls
TMWP LED - Traditional Wall Light Medium	4L - 4,000	UNV - 120 - 277V	DIM - Dim to 10% (0-10V)	50 - 5000K 40 - 4000K 30 - 3000K	BZA - Bronze BLK - Black SLV - Silver WHT - White	PCI120 - 120V Button Photocell PCI208-277 - 208-277V Button Photocell



Need more information?
[Click here for our glossary.](#)

Have additional questions?
 Call us at (800) 436-7800



PERFORMANCE

Delivered Lumens ⁷											
Lumen Package	CRI	3000K			4000K			5000K			Wattage
		Delivered Lumens	Efficacy	BUG Rating	Delivered Lumens	Efficacy	BUG Rating	Delivered Lumens	Efficacy	BUG Rating	
4L	80	3913	125	B1-U3-G3	3913	125	B1-U3-G3	4044	130	B1-U3-G3	31

Electrical Data - Current Draw AMPS ⁸				
Lumen Package	120V	208V	240V	277V
4L	0.26	0.15	0.13	0.11

⁸Electrical data at 25C (77F). Actual wattage may differ by +/-10%.

Energy Savings					
LED		HID			Annual Savings
Wattage	Annual Cost	Source Wattage	Total Wattage Used	Annual Cost	
27	\$12	50	72	\$52	\$40
		70	90	\$59	\$47
		100	129	\$77	\$65

Traditional Wall Light (TMWP) Medium

Type: _____

 Have questions? Call us at (800) 436-7800

PRODUCT DIMENSIONS

