

Prepared By :

Project : Date : ____

NYUE New York City Approved Universal Edge-lit

FEATURES & SPECIFICATIONS

Construction

- Meets City of New York Emergency Code requirements
- Pivoting single or double face acrylic panel for easy installation including wall, ceiling, sloped ceiling or recessed mounting
- All configurations are universal and includes:
 - Single-face clear panel
 - Double-face mirror panel
 - Surface mount braket
 - Back box and hanger bars for recessed mounting
- Extruded aluminum housing
- Tool-less panel installation with "snap-in" design
- All configurations include field-selectable directional chevrons
- Standard finish: White, Black, Satin Alumnium

U

SA

Optical

- Illuminated by long-life, high intensity red LEDs
- Fully-illuminated 8" characters with 1" stroke

Electrical

- Standard Universal Voltage 120/277VAC dual primary at 60Hz
- Low voltage disconnect eliminates deep discharge
- Brownout, short circuit and voltage surge protection
- Test button to provide manual verification of the transfer circuit and emergency lamps

Battery

- Maintenance free NiCad Battery
- Operating Temperature 0°C to 40°C (32°F to 104°F)



Installation

- Universal mounting:
 - Includes end or ceiling mounting bracket and all hardware for surface mounting.
 - Includes trim plate, hanger bars for grid install, and all hardware for recessed ceiling and recessed wall mounting applications. Electronics and battery contained in housing. Plug-in battery connector supplied for easy installation.

Warranty

- 5 year warranty on all electronics and housing.
- Separate 5 year pro-rated warranty on the battery.

Listings

- UL 924 Damp Location
- NFPA 101
- NEC
- UL Listed 90 minute emergency run time, 24 hour recharge time

ORDERING GUIDE

TYPICAL ORDER EXAMPLE:	NYUE
------------------------	------

Prefix	Letter Color	Housing Color	Options
NYUE - New York City Approved Universal Edge-lit	-lit U - Universal Surface and Recessed mounting, Single clear and Double mirror face	WH - White BK - Black	PA - Pendant Adapter
		SA - Satin Aluminum	

PRODUCT DIMENSIONS

