



4" Architectural Downlight (LAD4)

New Construction



OVERVIEW

Lumen Package (lm)	1,050 - 2,500
Wattage Range (W)	14 - 22
Efficacy Range (LPW)	93 - 112
Weight lbs (kg)	7.5 (3.4)

QUICK LINKS

FEATURES & SPECIFICATIONS

Optical System

- LED source provides superior lumen output with maximum visual comfort.
- Tailored spot, narrow flood, flood and wide flood beam optics designed for glare free illumination.
- Choice of flanged or flangeless spun reflector utilizing heavy gauge highly reflective diffuse anodized aluminum to deliver low glare, even illumination of the space.
- Reflectors are retained with three retention clips holding the flange tight to the finished ceiling surface.
- Minimum CRI of 80.

Electrical

- High-performance driver features over-voltage, under voltage, short-circuit and over temperature protection.
- 0 - 10V dimming (1% - 100%) standard.
- Standard Universal Voltage (120-277 Vac) Input 50/60 Hz.
- L70 Calculated Life: > 50k Hours projected @ 25°C per IESNA TM-21-11.
- Total harmonic distortion: <20%.
- Power factor: >.90.
- Input power stays constant over life.
- Driver can be accessed from below plenum for servicing.

- High-efficacy LEDs with integrated circuit board mount directly to an extruded aluminum heatsink to maximize heat dissipation and promote long life.
- Remote Emergency Battery (120-277V) is available to meet critical life safety lighting requirements. The 90-minute battery provides 7.8watts constant power to the LED system, ensuring code compliance. To calculate light output during emergency mode(EM battery 7.8 watts x LPW of fixture being powered - see spec sheet). Detailed wiring diagram and installation instructions can be located on the website..

Controls

- 0 - 10V dimming standard.
- Compatible with most 0-10V dimmers
- Compatible with LSI AirLink® Blue for networked controls
- See controls table for more information

New Construction Housing/ Plaster Frame

- Designed for use in non-insulated ceiling where insulation must be kept a minimum of 3" from the fixture.
- Junction box listed for (8) #12 AWG (four in, four out) 90°C conductors and thru branch wiring.
- Junction box contains (5) 1/2" knockouts with trade pry-out slots and (4) Romex cable clamp knockouts.

- Accommodates ceiling thickness up to 1.5".
- Plaster frame with collar is designed with 20-gauge colled rolled steel, black-painted
- Universal mounting brackets provide up to 5" vertical adjustment and accepts 1/2" EMT conduit.
- Additional channel bar, nailer bar and suspended ceiling accessories available. See accessories.
- Frame kit can be ordered separately for new construction build.

Installation

- Additional channel bar, nailer bar and suspended ceiling accessories available to accommodate a variety of ceiling types.

Warranty

- LSI luminaires carry a 5-year limited warranty. Refer to <https://www.lsicorp.com/resources/terms-conditions-warranty/> for more information.

Listings

- cETLus Listed to UL 1598 and UL 8750 standards for 25°C Ambient applications
- RoHS Compliant.
- EMI/RFI compliant with FCC 47CFR Part 15 Class B Consumer limits and Class A Commercial & Industrial.
- Damp location rated.
- Wet location rated with regressed lens.
- Title 24 Compliant.

4" Architectural Downlight (LAD4) New Construction

Type : _____

 **Have questions?** Call us at (800) 436-7800

ORDERING GUIDE

TYPICAL ORDER EXAMPLE: LAD4 LED 24L UNV DIM1 35 NF TR4R HAZ							
Prefix	Light Source	Lumen Package	Voltage	Driver	Color Temperature	CRI ²	Beam Optics ³
LAD4 - 4" New Construction ¹	LED	14L - 1,400 Lumens 24L - 2,400 Lumens	UNV - 120 - 277V	DIM1 - Dims to 1% (0-10V dimming)	27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K	Blank - 80 min.	SP - Spot NF - Narrow Flood FL - Flood WF - Wide Flood
Reflector			Finish				
Self-flanged	TR4R - Open Reflector		SF HAZ - Haze semi- diffused SF SPC - Specular clear				
	TR4RWW - Wall Wash ⁴		SF HAZ - Haze semi-diffused				
Flangeless (Ships standard w/ white plastic trim ring)	TR4R - Open Reflector		HAZ - Haze semi-diffused, white trim ring SPC - Specular clear, white trim ring				
	TR4RWW - Wall Wash ⁴		HAZ - Haze semi-diffused wall wash reflector, white trim ring				
	TR4RL - Regressed Lens ⁶		HAZ - Haze semi-diffused reflector w/ specular clear regressed lens and white trim ring SPC - Specular clear reflector w/ specular clear regressed lens and white trim ring				



Need more information?
Click here for our glossary

Have additional questions?
Call us at (800) 436-7800



ACCESSORY ORDERING INFORMATION

Part Number	Description
616105	WH - White metal trim ring (only compatible w/ flangeless trims)
205599	C27 - 27" channel bars (pair)
287522	C52 - 52" channel bars (pair)
345989	NB - Nailer bar kt (set of 4)
234808	SCIK - Suspended ceiling installation kit (set of 4 channel bars & 4 T-grid clips)
698364	BL1 - Black metal trim ring
778196	Remote Mount Battery
786277	Remote Battery with Grid Mount Kit ⁵
687986	New Construction Frame Kit-1 pack
791427	New Construction Frame Kit-2 pack
791429	New Construction Frame Kit-1 pack with Self-Diagnostic EM
791430	New Construction Frame Kit-2 pack with Self-Diagnostic EM
791431	T-Grid Bracket for EM ⁶

1 Housing can ship ahead of the light engine and reflector.

2 90 CRI requires 55 day leadtime & 100 MOQ; Consult Factory.

3 Self-flanged TR4RWW wall wash reflector comes with 40° integrated optic; additional beam optics not compatible.

4 Regressed lens trims are wet location listed. All other trims are rated for damp location.

5 For complete fixture with remote mount EM for T-Grid install, order remote battery with grid mount kit.

6 For new construction frame kit with EM for T-Grid install, order T-Grid bracket separately.

4" Architectural Downlight (LAD4) New Construction

Type : _____

 Have questions? Call us at (800) 436-7800

PERFORMANCE

DELIVERED LUMENS*										
Lumen Package	Distribution	2700K CCT		3000K CCT		3500K CCT		4000K CCT		Wattage
		Delivered Lumens	Efficacy							
14L	SP	1157	82.6	1157	82.6	1414	101.0	1414	101.0	14
	NF	1147	81.9	1146	81.9	1401	100.1	1401	100.1	
	FL	1134	81.0	1134	81.0	1386	99.0	1386	99.0	
	WF	1067	76.2	1067	76.2	1304	93.1	1304	93.1	
24L	SP	2008	91.3	2008	91.3	2455	111.6	2455	111.6	22
	NF	1989	90.4	1989	90.4	2432	110.5	2432	110.5	
	FL	1969	89.5	1969	89.5	2407	109.4	2407	109.4	
	WF	1852	84.2	1852	84.2	2264	102.9	2264	102.9	

*Electrical Data at 25C (77F)/ Actual Wattage may differ +/-10%

ELECTRICAL DATA (AMPS)*				
Lumen Package	120V	208V	240V	277V
14L	0.12	0.07	0.06	0.05
24L	0.18	0.11	0.09	0.08

*LED Chips are frequently updated therefore values may change.
Data is based on Haze Reflector.

4" Architectural Downlight (LAD4) New Construction

Type: _____

 **Have questions?** Call us at (800) 436-7800

PHOTOMETRICS

Luminaire photometry has been conducted by a NVLAP accredited testing laboratory in accordance with IESNA LM-79-08. As specified by IESNA LM-79-08 the entire luminaire is tested as the source resulting in a luminaire efficiency of 100%.

See the individual product page on <https://www.lsicorp.com/> for detailed photometric data.

LAD4-LED-24L-35-SP-TR4R-SF-HAZ

Lumens: 2,455


Watts: 22.2

Efficacy: 111


ZONAL LUMEN SUMMARY		
Zone	Lumens	%Fixture
0-10	803	32.7%
10-20	892	36.3%
20-30	569	23.2%
30-40	129	5.2%
40-50	43	1.7%
50-60	14	0.6%
60-70	3	0.1%
70-80	1	0.1%
80-90	0	0.0%
90-100	0	0.0%
0-180	2,455	100.0%

CANDELA TABLE	
Degree Vertical	Candela
0	5,756
5	5,523
10	4,611
15	3,473
20	2,446
25	1,609
30	685
35	275
40	136
45	76
50	39
55	15
60	5
65	3
70	2
75	1
80	0
85	0
90	0

Polar Candela Distribution



Illuminance at a Distance



■ Vert. Spread: 19.9°

■ Horiz. Spread 20.1°

LAD4-LED-24L-35-NF-TR4R-SF-HAZ

Lumens: 2,432


Watts: 22.2

Efficacy: 110


ZONAL LUMEN SUMMARY		
Zone	Lumens	%Fixture
0-10	497	20.4%
10-20	949	39.0%
20-30	710	29.2%
30-40	196	8.0%
40-50	60	2.5%
50-60	16	0.6%
60-70	3	0.1%
70-80	1	0.0%
80-90	0	0.0%
90-100	0	0.0%
0-180	2,432	100.0%

CANDELA TABLE	
Degree Vertical	Candela
0	5,756
5	5,523
10	4,611
15	3,473
20	2,446
25	1,609
30	685
35	275
40	136
45	76
50	39
55	15
60	5
65	3
70	2
75	1
80	0
85	0
90	0

Polar Candela Distribution



Illuminance at a Distance



■ Vert. Spread: 35.1°

■ Horiz. Spread 34.9°

4" Architectural Downlight (LAD4) New Construction

Type: _____

 Have questions? Call us at (800) 436-7800

PHOTOMETRICS

LAD4-LED-24L-35-FL-TR4R-SF-HAZ

Lumens: 2,407


Watts: 22.2

Efficacy: 108


ZONAL LUMEN SUMMARY		
Zone	Lumens	%Fixture
0-10	359	14.9%
10-20	884	36.7%
20-30	792	32.9%
30-40	265	11.0%
40-50	85	3.5%
50-60	18	0.7%
60-70	4	0.1%
70-80	1	0.1%
80-90	0	0.0%
90-100	0	0.0%
0-180	2,407	100.0%

CANDELA TABLE	
Degree Vertical	Candela
0	3,826
5	3,844
10	3,654
15	3,182
20	2,513
25	1,770
30	852
35	391
40	206
45	104
50	45
55	17
60	6
65	3
70	2
75	1
80	1
85	0
90	0

Polar Candela Distribution



Illuminance at a Distance



LAD4R-LED-24L-35-WF-TR4R-SF-HAZ

Lumens: 2,264


Watts: 22.2

Efficacy: 102


ZONAL LUMEN SUMMARY		
Zone	Lumens	%Fixture
0-10	237	10.5%
10-20	617	27.2%
20-30	722	31.9%
30-40	405	17.9%
40-50	219	9.7%
50-60	53	2.3%
60-70	9	0.4%
70-80	2	0.1%
80-90	0	0.0%
90-100	0	0.0%
0-180	2,264	100.0%

CANDELA TABLE	
Degree Vertical	Candela
0	3,826
5	3,844
10	3,654
15	3,182
20	2,513
25	1,770
30	852
35	391
40	206
45	104
50	45
55	17
60	6
65	3
70	2
75	1
80	1
85	0
90	0

Polar Candela Distribution



Illuminance at a Distance




4" Architectural Downlight (LAD4) New Construction

Type: _____

 Have questions? Call us at (800) 436-7800

PRODUCT DIMENSIONS



4" RECESSED DOWNLIGHT REFLECTORS



TR4R - Open Reflector
Self-Flange or Flangeless
HAZ - Haze semi-diffused
SPC - Specular clear



TR4RWW - Wall Wash w/ Kick Reflector
Self-Flange or Flangeless
HAZ - Haze semi-diffused



TR4RL - Regressed Lens w/ Specular Clear Reflector
Flangeless
HAZ - Haze semi-diffused
SPC - Specular clear
Wet Location Listed